



FIP Diaphragm valve Series: VMDC PVC-C Pneumatic operated Single acting, spring open Solvent cement spigots PN6

Characteristics

Series: VMDC

Housing construction: A [Weir type]

Housing material: PVC-C

Connection: Solvent cement spigots

Face to Face norm: Manufacturer standard

Actuator: Pneumatic operated

Operating principle: Single acting, spring open

With position indicator: No

Membrane material	External tube diameter of connection	Nominal inner diameter	Pressure rating	Face to Face length	Actuator material	Minimum medium temperature [continuous]	Maximum medium temperature [continuous]	Kv value	Article
	mm			mm		°C	°C	m³/h	
EPDM	75	DN65	PN6	284	PPG	0	90	1300	10052661
EPDM	90	DN80	PN6	300	PPG	0	90	2000	10052662
FPM (FKM)	75	DN65	PN6	284	PPG	0	90	1300	10052653
FPM (FKM)	90	DN80	PN6	300	PPG	0	90	2000	10052654
PTFE/EPDM	75	DN65	PN6	284	PPG	0	90	1300	10052669
PTFE/EPDM	90	DN80	PN6	300	PPG	0	90	2000	10052670

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.