



CMO Knifegate valve Type: 535 Cast iron Hand wheel Wafer type

This product will be phase-out soon by Type: 5402.

Characteristics

Type: 535
Norm: EN (DIN)
Housing construction: 1-part
Housing material: Cast iron
Material quality: EN-JL1040
Surface protection: Epoxy coating (in- and external)
Connection: Wafer type

Characteristics [2]

Type of sealing: Uni-directional
Spindle material: 1.4301
Material bracket: Steel
Actuator material: Ductile cast iron
Medium temperature: -10 / 120 °C

Nominal inner diameter	Pressure rating	Pressure rating flange	Face to Face norm	Face to Face length	Operation	Sealing	Plate material	Primary spindle seal material	Maximum pressure difference at 20 °C	Article
				mm					bar	
DN50	PN10	PN10	Manufacturer standard	40	Hand wheel, non-rising with rising stem	EPDM	1.4301	PTFE/EPDM	10	11239161
DN65	PN10	PN10	Manufacturer standard	40	Hand wheel, non-rising with rising stem	EPDM	1.4301	PTFE/EPDM	10	11239162
DN80	PN10	PN10	Manufacturer standard	50	Hand wheel, non-rising with rising stem	EPDM	1.4301	PTFE/EPDM	10	11239183
DN100	PN10	PN10	Manufacturer standard	50	Hand wheel, non-rising with rising stem	EPDM	1.4301	PTFE/EPDM	10	11239184
DN125	PN10	PN10	Manufacturer standard	50	Hand wheel, non-rising with rising stem	EPDM	1.4301	PTFE/EPDM	10	11239185
DN150	PN8	PN10	Manufacturer standard	60	Hand wheel, non-rising with rising stem	EPDM	1.4301	PTFE/EPDM	8	11239186
DN200	PN7	PN10	Manufacturer standard	60	Hand wheel, non-rising with rising stem	EPDM	1.4301	PTFE/EPDM	7	11239187
DN250	PN5	PN10	Manufacturer standard	70	Hand wheel, non-rising with rising stem	EPDM	1.4301	PTFE/EPDM	5	11239188
DN300	PN5	PN10	Manufacturer standard	70	Hand wheel, non-rising with rising stem	EPDM	1.4301	PTFE/EPDM	5	11239189
DN350	PN4	PN10	Manufacturer standard	96	Hand wheel, non-rising with rising stem	EPDM	1.4301	PTFE/EPDM	4	11239199
DN400	PN4	PN10	Manufacturer standard	100	Hand wheel, non-rising with rising stem	EPDM	1.4301	PTFE/EPDM	4	11239200
DN450	PN3	PN10	Manufacturer standard	106	Hand wheel, non-rising with rising stem	EPDM	1.4301	PTFE/EPDM	3	11239201

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Nominal inner diameter	Pressure rating	Pressure rating flange	Face to Face norm	Face to Face length	Operation	Sealing	Plate material	Primary spindle seal material	Maximum pressure difference at 20 °C	Article
				mm					bar	
DN500	PN3	PN10	Manufacturer standard	110	Hand wheel, non-rising with rising stem	EPDM	1.4301	PTFE/EPDM	3	11239202

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.