



TA Regulating valve Series: TBV-C Type: 26223 Static AMETAL Internal thread (BSPP)


Characteristics

Series: TBV-C
Type: 26223
Housing material: AMETAL
Material quality: Dezincification resistant brass
Connection: Internal thread (BSPP)
Type of control gear: Static
Application: CH water
With measuring nipples: Yes
Material disc: AMETAL
Spindle material: AMETAL

Material bonnet: AMETAL
Nipple material: AMETAL
Minimum medium temperature (continuous): -20 °C
Maximum medium temperature (continuous): 120 °C

Application

- Recommended in: Utilities



Nominal inner diameter	Pressure rating	Type of regulation	Control range	Kvs value	Kv value	Sealing	Article
				l/h	m³/h		
1/2" [15]	PN16	Open-close	0 / 900	0.9	0 / 0.9	EPDM	12160056
1/2" [15]	PN16	Open-close	0 / 1800	1.8	0 / 1.8	EPDM	12160059
3/4" [20]	PN16	Open-close	0 / 3400	3.4	0 / 3.4	EPDM	12160060
1" [25]	PN16	Open-close	0 / 7200	7.2	0 / 7.2	EPDM	12160062

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.