



GF Ball check valve Series: 561 PVDF Plastic welded sleeve PN16

Characteristics

Series: 561

Housing material: PVDF

Connection: Plastic welded sleeve

External tube diameter of connection	Pressure rating	Face to Face length	Valve shape	Sealing	Minimum medium temperature (continuous)	Maximum medium temperature (continuous)	Maximum pressure difference at 20 °C	Article
mm		mm			°C	°C	bar	
16	PN16	93	Ball	FPM (FKM)	-20	140	16	12301760
20	PN16	95	Ball	FPM (FKM)	-20	140	16	12301761
25	PN16	109	Ball	FPM (FKM)	-20	140	16	12301762
32	PN16	119	Ball	FPM (FKM)	-20	140	16	12301763
40	PN16	135	Ball	FPM (FKM)	-20	140	16	12301764
50	PN16	147	Ball	FPM (FKM)	-20	140	16	12301765
63	PN16	168	Ball	FPM (FKM)	-20	140	16	12301766

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.