



Check valve Type: 810 Stainless steel 304 Internal thread (BSPP) PN16

Characteristics

Type: 810


Norm: EN (DIN)

Construction type: Straight

Housing material: Roestvaststaal 304

Material quality: 1.4301

Connection: Internal thread (BSPP)



Nominal inner diameter	Pressure rating	Face to Face length	Valve shape	Sealing	Spring material	Minimum medium temperature (continuous)	Maximum medium temperature (continuous)	Maximum pressure difference at 20 °C	Article
		mm				°C	°C	bar	
3/8" [10]	PN16	56	Flap	FPM (FKM)	Stainless steel	-10	150	16	12615913
1/2" [15]	PN16	56	Flap	FPM (FKM)	Stainless steel	-10	150	16	10050462
3/4" [20]	PN16	67	Flap	FPM (FKM)	Stainless steel	-10	150	16	10050463
1" [25]	PN16	83	Flap	FPM (FKM)	Stainless steel	-10	150	16	10050461
1.1/4" [32]	PN16	97	Flap	FPM (FKM)	Stainless steel	-10	150	16	10050464
1.1/2" [40]	PN16	115	Flap	FPM (FKM)	Stainless steel	-10	150	16	11007771
2" [50]	PN16	121	Flap	FPM (FKM)	Stainless steel	-10	150	16	11105873

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.