



GOETZE Spring-loaded safety valve series 812sGK brass atmospheric discharge high capacity external thread

Characteristics

Series: 812sGK

Model: Spring-loaded

Housing material inlet side: Brass

Housing material outlet side: Brass

Medium temperature: -30 °C

Description	Article
Spring-loaded safety valve series 812sGK brass/FPM atmospheric discharge adjustment range 0,2 - 30,0 barg 1" BSPP	14058866
Spring-loaded safety valve series 812sGK brass/FPM atmospheric discharge adjustment range 0,2 - 30,0 barg 1.1/2" BSPP	14058868
Spring-loaded safety valve series 812sGK brass/FPM atmospheric discharge adjustment range 0,2 - 30,0 barg 1/2" BSPP	14058864
Spring-loaded safety valve series 812sGK brass/FPM atmospheric discharge adjustment range 0,2 - 30,0 barg 2" BSPP	14058869
Spring-loaded safety valve series 812sGK brass/FPM atmospheric discharge adjustment range 0,2 - 30,0 barg 1.1/4" BSPP	14058867
Spring-loaded safety valve series 812sGK brass/FPM atmospheric discharge adjustment range 0,2 - 30,0 barg 3/4" BSPP	14058865

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.