



LEADER Spiral-wound gasket SRI 316L/316L/P/316L EN 1514-2

Characteristics

Series: SRI

Type: Spiral with inside and outside ring

Norm: EN 1514-2

Inside ring material: Stainless steel 316L

Spiral material: Stainless steel 316L

Material filler: Polytetrafluoroethylene (PTFE)

Centring ring material: Stainless steel 316L

Temperature range: -200 / 260 °C

Suitable for medium: Water [process water],

Chemicals, Caustics, Aqueous solutions, Acids,

Pharma, Cryogenic, Moderate Acids, Natural gas, Air

[compressed air], Lubricant, Gases, Alkalies, Water,

Weak Acids, Weak Alkalies

Approval according to: EN10.204 3.1, TA-Luft

Spiral ring thickness: 4.5 mm

Inside ring thickness: 3 mm

Application

- Recommended in: Food & Beverages

Flange pressure stage	Nominal diameter	Article
PN10/40	DN15	11100443
PN10/40	DN32	11100444
PN10/40	DN40	11044722
PN10/40	DN50	11044730
PN10/40	DN65	11100445
PN10/40	DN80	11044735
PN25/40	DN100	11100446

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.