



JC 3-Way ball valve Series: 916IIT Type: 3505 Stainless steel Flange PN16

Characteristics

Series: 916IIT

Type: 3505

Norm: EN (DIN)

Construction type: 3-way

Housing material: Stainless steel

Material quality: 1.4408

Connection: Flange

Tertiary spindle seal material: Graphite

Actuator material: ASTM A216 WCB

Minimum medium temperature (continuous): -50 °C

Maximum medium temperature (continuous): 230 °C

Application

- Heavy-duty industrial applications up to 16 bar.
- Liquid and gaseous media.
- Recommended in: Chemical

Technical Information

- Flanged connection in accordance with EN 1092-1.
- Designed with L or T bore.
- Pressure class PN16.
- With top-flange in accordance with ISO 5211.
- Media temperature: -50/+230°C.
- DN25 to DN150 with handle.
- The 3-way ball valve (floating ball) is intended to be used as a distribution valve. Pressure on the "closed" outlet may lead to leakages at the other outlets (medium).

Construction


- Design in accordance with EN 12516 and EN 1983.
- Full flow capacity.
- Equipped with antistatic design between ball and housing.
- All wet parts comply with NACE MR 0175/ISO 15156 & AMP, NACE MR 0103/ISO 17945.

Approval

- Safety integrity level (SIL) LEVEL 3 IEC 61508.
- Certified in accordance with FDA, USP CLASS VI CONFORMITY (CE 1935/2004).

Options

- Equipped with worm gearbox and pneumatic, electric or hydraulic actuators.
- Position feedback for manual or automated valves.
- Stainless steel extended spindle type: 3222 for insulation.
- Available in class 150 (series 915).
- Also available as a four-way ball valve.



Size table:

DN	d mm	L mm	H mm	M mm	Weight kg
DN25	25	212	96	170	8
DN40	40	262	121	200	17
DN50	50	290	134	350	25
DN65	65	325	180	350	34
DN80	80	370	200	465	51
DN100	100	430	240	475	77
DN150	150	500	280	855	138

Nominal inner diameter	Pressure rating	Manual operation	Mounting flange	Ball bore	Bore	Material ball	Seat material	Spindle material	Primary spindle seal material	Article
DN25	PN16	Handle	F05	T-bore	Full bore	Stainless steel	PTFE	ASTM A479 316	RPTFE	11022581
DN25	PN16	Handle	F05	L-bore	Full bore	Stainless steel	PTFE	ASTM A479 316	RPTFE	11080963
DN40	PN16	Handle	F07	L-bore	Full bore	Stainless steel	PTFE	ASTM A479 316	RPTFE	10054032
DN40	PN16	Handle	F07	T-bore	Full bore	Stainless steel	PTFE	ASTM A479 316	RPTFE	11339891
DN50	PN16	Handle	F07	T-bore	Full bore	Stainless steel	PTFE	ASTM A479 316	RPTFE	10054036
DN50	PN16	Handle	F07	L-bore	Full bore	Stainless steel	PTFE	ASTM A479 316	RPTFE	10054033
DN65	PN16	Handle	F10	T-bore	Full bore	Stainless steel	PTFE	ASTM A479 316	RPTFE	10054037
DN65	PN16	Handle	F10	L-bore	Full bore	Stainless steel	PTFE	ASTM A479 316	RPTFE	10054034
DN80	PN16	Handle	F10	T-bore	Full bore	Stainless steel	PTFE	ASTM A479 316	RPTFE	10054038
DN80	PN16	Handle	F10	L-bore	Full bore	Stainless steel	PTFE	ASTM A479 316	RPTFE	10054035
DN100	PN16	Handle	F12	T-bore	Full bore	Stainless steel	PTFE	ASTM A479 316	RPTFE	11069994
DN100	PN16	Handle	F12	L-bore	Full bore	Stainless steel	PTFE	ASTM A479 316	RPTFE	11091934
DN150	PN16	Handle	F14	L-bore	Full bore	Stainless steel	PTFE	ASTM A479 316	RPTFE	13277173
DN150	PN16	Handle	F14	T-bore	Full bore	Stainless steel	PTFE	ASTM A479 316	RPTFE	13277176

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.