


3-Way ball valve Type: 7327 Ductile cast iron Flange PN16



Characteristics

- Type: 7327
- Norm: EN (DIN)
- Construction type: 3-way
- Housing material: Ductile cast iron
- Material quality: EN-JS1030
- Surface protection: Paint min. 60 µm
- Connection: Flange
- Angular rotation: 120 °
- Minimum medium temperature (continuous): -20 °C
- Maximum medium temperature (continuous): 150 °C



Nominal inner diameter	Pressure rating	Manual operation	Ball bore	Bore	Material ball	Seat material	Spindle material	Primary spindle seal material	Actuator material	Article
DN50	PN16	Handle	L-bore	Full bore	1.4301	TFM 1600	1.4301	PTFE	Steel	11814298
DN65	PN16	Handle	L-bore	Full bore	1.4301	TFM 1600	1.4301	PTFE	Steel	11814299
DN80	PN16	Handle	L-bore	Full bore	1.4301	TFM 1600	1.4301	PTFE	Steel	11814300
DN100	PN16	Handle	L-bore	Full bore	1.4301	TFM 1600	1.4301	PTFE	Steel	11814301
DN125	PN16	Handle	L-bore	Full bore	1.4301	TFM 1600	1.4301	PTFE	Steel	11814302
DN150	PN16	Handle	L-bore	Full bore	1.4301	TFM 1600	1.4301	PTFE	Steel	11814303

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.