



DURAPIPE 3-Way ball valve Series: TKD ABS Glued sleeve PN16

Characteristics

Series: TKD

Construction type: 3-way

Housing material: ABS

Connection: Glued sleeve

Angular rotation: 90 °

Seat material: PTFE

Primary spindle seal material: EPDM

Secondary spindle seal material: EPDM

Body seal: EPDM

Nominal inner diameter	External tube diameter of connection	Pressure rating	Face to Face norm	Manual operation	Ball bore	Bore	Material ball	Minimum medium temperature (continuous)	Maximum medium temperature (continuous)	Article
	mm							°C	°C	
DN15	20			Handle	L-bore		ABS			11606995
DN15	20	PN16	Manufacturer standard	Handle	T-bore	Full bore	ABS	-40	70	11607001
DN20	25	PN16	Manufacturer standard	Handle	T-bore	Full bore	ABS	-40	70	11607002
DN20	25	PN16	Manufacturer standard	Handle	L-bore	Full bore	ABS	-40	70	11606996
DN25	32	PN16	Manufacturer standard	Handle	T-bore	Full bore	ABS	-40	70	11607003
DN25	32	PN16	Manufacturer standard	Handle	L-bore	Full bore	ABS	-40	70	11606997
DN32	40	PN16	Manufacturer standard	Handle	T-bore	Full bore	ABS	-40	70	11607004
DN32	40	PN16	Manufacturer standard	Handle	L-bore	Full bore	ABS	-40	70	11606998
DN40	50	PN16	Manufacturer standard	Handle	L-bore	Full bore	ABS	-40	70	11606999
DN40	50	PN16	Manufacturer standard	Handle	T-bore	Full bore	ABS	-40	70	11607005
DN50	63			Handle	L-bore	Full bore	ABS			11607000
DN50	63	PN16	Manufacturer standard	Handle	T-bore	Full bore	ABS	-40	70	11607006

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.