

15JP

GATES Power band Predator® narrow section 15JP

Characteristics

Series: Predator® Powerband®**Type:** 5V/15JP**Height:** 13 mm**Width (top):** 16 mm**Material:** CR (polychloroprene)**Tensile Cord:** Aramid**Sheathed:** Yes**Temperature resistance:** -30 / 60 °C

Number of ribs	Effective length (ISO)	Outside length	Outside length	Article
	mm	mm	in	
2	1600	4064	160	11539341
2	1700	4318	170	11539345
2	1800	4572	180	11539349
2	1900	4826	190	11539353
2	3000	7620	300	11539385
2	3350	8509	335	11539393
2	3550	9017	355	11539397
2	6000	15240	600	11539433
2	7100	18034	710	11539445
2	8000	20320	800	11539453
2	8500	21590	850	12067711
2	9000	22860	900	11539457
3	1600	4064	160	11539342
3	1700	4318	170	11539346
3	1800	4572	180	11539350
3	1900	4826	190	11539354
3	3000	7620	300	11539386
3	3350	8509	335	11539394
3	3550	9017	355	11539398
3	6000	15240	600	11539434
3	7100	18034	710	11539446
3	8000	20320	800	11539454
3	8500	21590	850	12067712
3	9000	22860	900	11539458
4	1600	4064	160	11539343
4	1700	4318	170	11539347
4	1800	4572	180	11539351
4	1900	4826	190	11539355
4	3000	7620	300	11539387
4	3350	8509	335	11539395
4	3550	9017	355	11539399
4	6000	15240	600	11539435
4	7100	18034	710	11539447
4	8000	20320	800	11539455
4	8500	21590	850	12067713
4	9000	22860	900	11539459
5	1600	4064	160	11539344
5	1700	4318	170	11539348
5	1800	4572	180	11539352

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Number of ribs	Effective length (ISO)	Outside length		Article
	mm	mm	in	
5	1900	4826	190	11539356
5	3000	7620	300	11539388
5	3350	8509	335	11539396
5	3550	9017	355	11539400
5	6000	15240	600	11539436
5	7100	18034	710	11539448
5	8000	20320	800	11539456
5	8500	21590	850	12067714
5	9000	22860	900	11539460
6	1600	4064	160	12067278
6	1700	4318	170	12067293
6	1800	4572	180	12067308
6	1900	4826	190	12067324
6	3000	7620	300	12067444
6	3350	8509	335	12067474
6	3350	9017	355	12067475
6	6000	15240	600	12067625
6	7100	18034	710	12067670
6	8000	20320	800	12067700
6	8500	21590	850	12067715
6	9000	22860	900	12067730
7	1600	4064	160	12067279
7	1700	4318	170	12067294
7	1800	4572	180	12067309
7	1900	4826	190	12067325
7	3000	7620	300	12067445
7	3350	8509	335	12067476
7	3550	9017	355	12067490
7	6000	15240	600	12067626
7	7100	18034	710	12067671
7	8000	20320	800	12067701
7	8500	21590	850	12067716
7	9000	22860	900	12067731
8	1600	4064	160	12067280
8	1700	4318	170	12067295
8	1800	4572	180	12067310
8	1900	4826	190	12067326
8	3000	7620	300	12067446
8	3350	8509	335	12067477
8	3550	9017	355	12067491
8	6000	15240	600	12067627
8	7100	18034	710	12067672
8	8000	20320	800	12067702
8	8500	21590	850	12067717
8	9000	22860	900	12067732
9	1600	4064	160	12067281
9	1700	4318	170	12067296
9	1800	4572	180	12067311
9	1900	4826	190	12067327
9	3000	7620	300	12067447
9	3350	8509	335	12067478
9	3550	9017	355	12067492
9	6000	15240	600	12067628

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Number of ribs	Effective length (ISO)	Outside length	Outside length	Article
	mm	mm	in	
9	6700	18034	710	12067673
9	8000	20320	800	12067703
9	8500	21590	850	12067718
9	9000	22860	900	12067733
10	1600	4064	160	12067282
10	1700	4318	170	12067297
10	1800	4572	180	12067313
10	1900	4826	190	12067328
10	3000	7620	300	12067448
10	3350	8509	335	12067479
10	3550	9017	355	12067493
10	6000	15240	600	12067629
10	6700	18034	710	12067674
10	8000	20320	800	12067704
10	8500	21590	850	12067719
10	9000	22860	900	12067734
11	1600	4064	160	12067283
11	1700	4318	170	12067298
11	1800	4572	180	12067314
11	1900	4826	190	12067329
11	3000	7620	300	12067449
11	3350	8509	335	12067480
11	3550	9017	355	12067494
11	6000	15240	600	12067630
11	6700	18034	710	12067675
11	8000	20320	800	12067705
11	8500	21590	850	12067720
11	9000	22860	900	12067735
12	1600	4064	160	12067284
12	1700	4318	170	12067299
12	1800	4572	180	12067315
12	1900	4826	190	12067330
12	3000	7620	300	12067450
12	3350	8509	335	12067481
12	3550	9017	355	12067495
12	6000	15240	600	12067631
12	6700	18034	710	12067676
12	8000	20320	800	12067706
12	8500	21590	850	12067721
12	9000	22860	900	12067736
13	1600	4064	160	12067285
13	1700	4318	170	12067300
13	1800	4572	180	12067316
13	1900	4826	190	12067331
13	3000	7620	300	12067451
13	3350	8509	335	12067482
13	3550	9017	355	12067496
13	6000	15240	600	12067632
13	6700	18034	710	12067677
13	8000	20320	800	12067707
13	8500	21590	850	12067722
13	9000	22860	900	12067737
14	1600	4064	160	12067286

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Number of ribs	Effective length (ISO)	Outside length	Outside length	Article
	mm	mm	in	
14	1700	4318	170	12067301
14	1800	4572	180	12067317
14	1900	4826	190	12067332
14	3000	7620	300	12067452
14	3350	8509	335	12067483
14	3550	9017	355	12067497
14	6000	15240	600	12067633
14	6700	18034	710	12067678
14	8000	20320	800	12067708
14	8500	21590	850	12067723
14	9000	22860	900	12067738
15	1600	4064	160	12067287
15	1700	4318	170	12067302
15	1800	4572	180	12067318
15	1900	4826	190	12067333
15	3000	7620	300	12067453
15	3350	8509	335	12067484
15	3550	9017	355	12067498
15	6000	15240	600	12067634
15	6700	18034	710	12067679
15	8000	20320	800	12067709
15	8500	21590	850	12067724
15	9000	22860	900	12067739
16	1600	4064	160	12067288
16	1700	4318	170	12067303
16	1800	4572	180	12067319
16	1900	4826	190	12067334
16	3000	7620	300	12067454
16	3350	8509	335	12067485
16	3550	9017	355	12067499
16	6000	15240	600	12067635
16	6700	18034	710	12067680
16	8000	20320	800	12067710
16	8500	21590	850	12067725
16	9000	22860	900	12067740

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.