

 3M-JB

GATES Power band Polyflex® Multiple polyurethane V-belt section 3M/JB



Characteristics

Series: Polyflex® JB

Type: 3M/JB

Height: 2.28 mm

Width (top): 3 mm

Material: PU (Polyurethane)

Tensile Cord: Polyester (PES)

Temperature resistance: -54 / 60 °C

Pitch mm	Number of ribs	Effective length (ISO) mm	Article
3.35	2	175	12068614
3.35	2	180	12068616
3.35	2	185	12068618
3.35	2	190	12068620
3.35	2	195	12068622
3.35	2	200	12068624
3.35	2	206	12068626
3.35	2	212	12068629
3.35	2	218	12068631
3.35	2	224	12068633
3.35	2	230	12068635
3.35	2	236	12068637
3.35	2	243	12068639
3.35	2	250	12068641
3.35	2	258	12068643
3.35	2	265	12068645
3.35	2	272	12068647
3.35	2	280	12068649
3.35	2	290	12068651
3.35	2	300	12068653
3.35	2	307	12068655
3.35	2	315	12068657
3.35	2	319	12068659
3.35	2	325	12068661
3.35	2	335	12068663
3.35	2	345	12068665
3.35	2	350	12068667
3.35	2	355	12068669
3.35	2	365	12068671
3.35	2	375	12068673
3.35	2	387	12068675
3.35	2	400	12068677
3.35	2	406	12068679
3.35	2	412	12068681
3.35	2	425	12068683
3.35	2	437	12068685
3.35	2	450	12068687
3.35	2	462	12068689
3.35	2	475	12068691

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Pitch mm	Number of ribs	Effective length (ISO) mm	Article
3.35	2	487	12068693
3.35	2	500	12068695
3.35	2	515	12068697
3.35	2	530	12068699
3.35	2	545	12068701
3.35	2	553	12068703
3.35	2	560	12068705
3.35	2	580	12068707
3.35	2	600	12068709
3.35	2	615	12068711
3.35	2	630	12068713
3.35	2	650	12068715
3.35	2	670	12068717
3.35	2	690	12068719
3.35	2	710	12068721
3.35	2	730	12068723
3.35	2	750	12068725
3.35	3	175	12068615
3.35	3	180	12068617
3.35	3	185	12068619
3.35	3	190	12068621
3.35	3	195	12068623
3.35	3	200	12068625
3.35	3	206	12068628
3.35	3	212	12068630
3.35	3	218	12068632
3.35	3	224	12068634
3.35	3	230	12068636
3.35	3	236	12068638
3.35	3	243	12068640
3.35	3	250	12068642
3.35	3	258	12068644
3.35	3	265	12068646
3.35	3	272	12068648
3.35	3	280	12068650
3.35	3	290	12068652
3.35	3	300	12068654
3.35	3	307	12068656
3.35	3	315	12068658
3.35	3	319	12068660
3.35	3	325	12068662
3.35	3	335	12068664
3.35	3	345	12068666
3.35	3	350	12068668
3.35	3	355	12068670
3.35	3	365	12068672
3.35	3	375	12068674
3.35	3	387	12068676
3.35	3	400	12068678
3.35	3	406	12068680
3.35	3	412	12068682
3.35	3	425	12068684
3.35	3	437	12068686

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Pitch mm	Number of ribs	Effective length (ISO) mm	Article
3.35	3	450	12068688
3.35	3	462	12068690
3.35	3	487	12068694
3.35	3	500	12068696
3.35	3	515	12068698
3.35	3	530	12068700
3.35	3	545	12068702
3.35	3	553	12068704
3.35	3	560	12068706
3.35	3	580	12068708
3.35	3	600	12068710
3.35	3	630	12068714
3.35	3	650	12068716
3.35	3	670	12068718
3.35	3	710	12068722
3.35	3	730	12068724
3.35	3	750	12068726

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.