



GATES Power band Predator® narrow section SPCP

Characteristics

Series: Predator® Powerband®

Type: SPCP

Height: 18 mm

Width (top): 22 mm

Material: CR (polychloroprene)

Tensile Cord: Aramid

Sheathed: Yes

Temperature resistance: -30 / 60 °C



Number of ribs	Reference length (ISO)	Article
	mm	Max. 200 articles in the table
2	3000	11539172
2	3150	11539176
2	3350	11539180
2	3550	11539184
2	3750	11539188
2	4000	11539192
2	4250	11539196
2	4500	11539200
2	4750	11539204
2	5000	11539208
2	5300	11539212
2	5600	11539216
2	6000	11539220
2	6300	11539224
2	6700	11539228
2	7100	11539232
2	7500	11539236
2	8000	11539240
2	8500	11539244
2	9000	11539248
2	10000	11539252
2	10600	11539256
2	11200	11539260
3	3000	11539173
3	3150	11539177
3	3350	11539181
3	3550	11539185
3	3750	11539189
3	4000	11539193
3	4500	11539201
3	4750	11539205
3	5000	11539209
3	5300	11539213
3	5600	11539217
3	6000	11539221
3	6300	11539225
3	6700	11539229
3	7100	11539233
3	7500	11539237

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Number of ribs	Reference length (ISO)	Article
	mm	Max. 200 articles in the table
3	8000	11539241
3	8500	11539245
3	9000	11539249
3	10000	11539253
3	10600	11539257
3	11200	11539261
4	3000	11539174
4	3150	11539178
4	3350	11539182
4	3550	11539186
4	3750	11539190
4	4000	11539194
4	4250	11539198
4	4500	11539202
4	4750	11539206
4	5000	11539210
4	5300	11539214
4	5600	11539218
4	6000	11539222
4	6300	11539226
4	6700	11539230
4	7100	11539234
4	7500	11539238
4	8000	11539242
4	8500	11539246
4	9000	11539250
4	10000	11539254
4	10600	11539258
4	11200	11539262
5	3000	11539175
5	3150	11539179
5	3350	11539183
5	3550	11539187
5	3750	11539191
5	4000	11539195
5	4250	11539199
5	4500	11539203
5	4750	11539207
5	5000	11539211
5	5300	11539215
5	5600	11539219
5	6000	11539223
5	6300	11539227
5	6700	11539231
5	7100	11539235
5	7500	11539239
5	8000	11539243
5	8500	11539247
5	9000	11539251
5	10000	11539255
5	10600	11539259
5	11200	11539263
6	3000	12066735

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Number of ribs	Reference length (ISO)	Article
	mm	Max. 200 articles in the table
6	3150	12066746
6	3350	12066756
6	3550	12066767
6	3750	12066778
6	4000	12066789
6	4250	12066800
6	4500	12066811
6	4750	12066822
6	5000	12066833
6	5300	12066844
6	5600	12066855
6	6000	12066866
6	6300	12066877
6	7100	12066899
7	3000	12066736
7	3150	12066747
7	3350	12066757
7	3550	12066768
7	3750	12066779
7	4000	12066790
7	4250	12066801
7	4500	12066812
7	4750	12066823
7	5000	12066834
7	5300	12066845
7	5600	12066856
7	6000	12066867
7	6300	12066878
7	6700	12066889
7	7100	12066900
8	3000	12066737
8	3150	12066748
8	3350	12066758
8	3550	12066769
8	3750	12066780
8	4000	12066791
8	4250	12066802
8	4500	12066813
8	4750	12066824
8	5300	12066846
8	5600	12066857
8	6000	12066868
8	6300	12066879
8	6700	12066890
8	7100	12066901
9	3000	12066738
9	3150	12066749
9	3350	12066759
9	3550	12066770
9	3750	12066781
9	4000	12066792
9	4250	12066803
9	4500	12066814

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Number of ribs	Reference length (ISO)	Article
	mm	Max. 200 articles in the table
9	4750	12066825
9	5000	12066836
9	5300	12066847
9	5600	12066858
9	6000	12066869
9	6300	12066880
9	6700	12066891
9	7100	12066902
10	3000	12066739
10	3150	12066750
10	3350	12066760
10	3550	12066771
10	3750	12066782
10	4000	12066793
10	4250	12066804
10	4500	12066815
10	4750	12066826
10	5000	12066837
10	5300	12066848
10	5600	12066859
10	6000	12066870
10	6300	12066881
10	6700	12066892
10	7100	12066903
11	3000	12066740
11	3150	12066751
11	3350	12066761
11	3550	12066772
11	3750	12066783
11	4000	12066794
11	4250	12066805
11	4500	12066816
11	4750	12066827
11	5000	12066838
11	5300	12066849
11	5600	12066860
11	6000	12066871
11	6300	12066882
11	6700	12066893
11	7100	12066904
12	3000	12066741
12	3350	12066762
12	3550	12066773
12	3750	12066784
12	4000	12066795
12	4250	12066806
12	4500	12066817
12	4750	12066828
12	5000	12066839
12	5300	12066850
12	5600	12066861
12	6000	12066872
12	6300	12066883

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Number of ribs	Reference length (ISO)	Article
	mm	Max. 200 articles in the table
12	6700	12066894

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.