



NORGREN ISO Roundline cylinder double acting serie RM/8000/M

- Magnetic piston as standard
- Conforms to ISO 6432
- High strength, double crimped end cap design
- Corrosion resistant
- Buffer or adjustable cushioning
- Nose mounting nut and piston rod locknut as standard

Characteristics

Series: RM/8000/M

Type: RM/8000/M

Function: Double acting

Magnetic: Yes

Barrel material: Stainless steel

Operating temperature: -10 / 80 °C

Manufacturer ID	Cushioning	Bore diameter	Stroke length	Port Size	Port Size	Operating pressure	Article
		mm	mm				
RM/8017/M/10	Adjustable	16	10	M 5		1 / 10	11578993
RM/8017/M/15	Adjustable	16	15	M 5		1 / 10	11578997
RM/8017/M/20	Adjustable	16	20	M 5		1 / 10	11578999
RM/8017/M/25	Adjustable	16	25	M 5		1 / 10	11579001
RM/8017/M/35	Adjustable	16	35	M 5		1 / 10	11579003
RM/8017/M/40	Adjustable	16	40	M 5		1 / 10	11579005
RM/8017/M/50	Adjustable	16	50	M 5		1 / 10	11579006
RM/8017/M/70	Adjustable	16	70	M 5		1 / 10	11579007
RM/8017/M/80	Adjustable	16	80	M 5		1 / 10	11579008
RM/8017/M/90	Adjustable	16	90	M 5		1 / 10	11579009
RM/8017/M/100	Adjustable	16	100	M 5		1 / 10	11578994
RM/8017/M/125	Adjustable	16	125	M 5		1 / 10	11578995
RM/8017/M/140	Adjustable	16	140	M 5		1 / 10	11578996
RM/8017/M/160	Adjustable	16	160	M 5		1 / 10	11578998
RM/8017/M/200	Adjustable	16	200	M 5		1 / 10	11579000
RM/8017/M/300	Adjustable	16	300	M 5		1 / 10	11579002
RM/8017/M/350	Adjustable	16	350	M 5		1 / 10	11579004
RM/8021/M/10	Adjustable	20	10		G1/8	1 / 10	11579052
RM/8021/M/20	Adjustable	20	20		G1/8	1 / 10	11579058
RM/8021/M/25	Adjustable	20	25		G1/8	1 / 10	11579061
RM/8021/M/30	Adjustable	20	30		G1/8	1 / 10	11579063
RM/8021/M/40	Adjustable	20	40		G1/8	1 / 10	11579066
RM/8021/M/50	Adjustable	20	50		G1/8	1 / 10	11579067
RM/8021/M/60	Adjustable	20	60		G1/8	1 / 10	11579068
RM/8021/M/65	Adjustable	20	65		G1/8	1 / 10	11579069
RM/8020/M/75	Adjustable	20	75		G1/8	1 / 10	11579036
RM/8021/M/80	Adjustable	20	80		G1/8	1 / 10	11579071
RM/8021/M/90	Adjustable	20	90		G1/8	1 / 10	11579073
RM/8021/M/100	Adjustable	20	100		G1/8	1 / 10	11579053
RM/8021/M/125	Adjustable	20	125		G1/8	1 / 10	11579054
RM/8021/M/140	Adjustable	20	140		G1/8	1 / 10	11579055
RM/8021/M/150	Adjustable	20	150		G1/8	1 / 10	11579056
RM/8021/M/160	Adjustable	20	160		G1/8	1 / 10	11579057

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Manufacturer ID	Cushioning	Bore diameter	Stroke length	Port Size mm	Port Size in	Operating pressure bar	Article
		mm	mm				
RM/8021/M/200	Adjustable	20	200		G1/8	1 / 10	11579059
RM/8021/M/230	Adjustable	20	230		G1/8	1 / 10	11579060
RM/8021/M/250	Adjustable	20	250		G1/8	1 / 10	11579062
RM/8021/M/300	Adjustable	20	300		G1/8	1 / 10	11579064
RM/8021/M/320	Adjustable	20	320		G1/8	1 / 10	11579065
RM/8021/M/700	Adjustable	20	700		G1/8	1 / 10	11579070
RM/8021/M/800	Adjustable	20	800		G1/8	1 / 10	11579072
RM/8026/M/1000	Adjustable	25	1		G1/8	1 / 10	11579133
RM/8026/M/10	Adjustable	25	10		G1/8	1 / 10	11579131
RM/8026/M/15	Adjustable	25	15		G1/8	1 / 10	11579136
RM/8026/M/20	Adjustable	25	20		G1/8	1 / 10	11579141
RM/8026/M/23	Adjustable	25	23		G1/8	1 / 10	11579144
RM/8026/M/25	Adjustable	25	25		G1/8	1 / 10	11579145
RM/8026/M/30	Adjustable	25	30		G1/8	1 / 10	11579147
RM/8026/M/35	Adjustable	25	35		G1/8	1 / 10	11579150
RM/8026/M/40	Adjustable	25	40		G1/8	1 / 10	11579152
RM/8026/M/125	Adjustable	25	125		G1/8	1 / 10	11579134
RM/8026/M/140	Adjustable	25	140		G1/8	1 / 10	11579135
RM/8026/M/150	Adjustable	25	150		G1/8	1 / 10	11579137
RM/8026/M/160	Adjustable	25	160		G1/8	1 / 10	11579138
RM/8026/M/178	Adjustable	25	178		G1/8	1 / 10	11579139
RM/8026/M/180	Adjustable	25	180		G1/8	1 / 10	11579140
RM/8026/M/200	Adjustable	25	200		G1/8	1 / 10	11579142
RM/8026/M/220	Adjustable	25	220		G1/8	1 / 10	11579143
RM/8026/M/250	Adjustable	25	250		G1/8	1 / 10	11579146
RM/8026/M/300	Adjustable	25	300		G1/8	1 / 10	11579148
RM/8026/M/320	Adjustable	25	320		G1/8	1 / 10	11579149
RM/8026/M/350	Adjustable	25	350		G1/8	1 / 10	11579151
RM/8026/M/400	Adjustable	25	400		G1/8	1 / 10	11579153
RM/8026/M/420	Adjustable	25	420		G1/8	1 / 10	11579154
RM/8010/M/5	Mechanical	10	5	M 5		1 / 10	11578911
RM/8010/M/10	Mechanical	10	10	M 5		1 / 10	11578902
RM/8010/M/15	Mechanical	10	15	M 5		1 / 10	11578905
RM/8010/M/20	Mechanical	10	20	M 5		1 / 10	11578907
RM/8010/M/25	Mechanical	10	25	M 5		1 / 10	11578908
RM/8010/M/30	Mechanical	10	30	M 5		1 / 10	11578909
RM/8010/M/40	Mechanical	10	40	M 5		1 / 10	11578910
RM/8010/M/50	Mechanical	10	50	M 5		1 / 10	11578912
RM/8010/M/60	Mechanical	10	60	M 5		1 / 10	11578913
RM/8010/M/80	Mechanical	10	80	M 5		1 / 10	11578914
RM/8010/M/100	Mechanical	10	100	M 5		1 / 10	11578903
RM/8010/M/110	Mechanical	10	110	M 5		1 / 10	11578904
RM/8010/M/170	Mechanical	10	170	M 5		1 / 10	11578906
RM/8012/M/10	Mechanical	12	10	M 5		1 / 10	11578915
RM/8012/M/15	Mechanical	12	15	M 5		1 / 10	11578919
RM/8012/M/20	Mechanical	12	20	M 5		1 / 10	11578923
RM/8012/M/25	Mechanical	12	25	M 5		1 / 10	11578925
RM/8012/M/30	Mechanical	12	30	M 5		1 / 10	11578927
RM/8012/M/35	Mechanical	12	35	M 5		1 / 10	11578929
RM/8012/M/40	Mechanical	12	40	M 5		1 / 10	11578930
RM/8012/M/50	Mechanical	12	50	M 5		1 / 10	11578931
RM/8012/M/60	Mechanical	12	60	M 5		1 / 10	11578932

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Manufacturer ID	Cushioning	Bore diameter	Stroke length	Port Size	Port Size	Operating pressure	Article
		mm	mm	mm	in	bar	
RM/8012/M/65	Mechanical	12	65	M 5		1 / 10	11578933
RM/8012/M/70	Mechanical	12	70	M 5		1 / 10	11578935
RM/8012/M/80	Mechanical	12	80	M 5		1 / 10	11578936
RM/8012/M/100	Mechanical	12	100	M 5		1 / 10	11578916
RM/8012/M/125	Mechanical	12	125	M 5		1 / 10	11578917
RM/8012/M/140	Mechanical	12	140	M 5		1 / 10	11578918
RM/8012/M/150	Mechanical	12	150	M 5		1 / 10	11578920
RM/8012/M/160	Mechanical	12	160	M 5		1 / 10	11578921
RM/8012/M/175	Mechanical	12	175	M 5		1 / 10	11578922
RM/8012/M/200	Mechanical	12	200	M 5		1 / 10	11578924
RM/8012/M/250	Mechanical	12	250	M 5		1 / 10	11578926
RM/8012/M/300	Mechanical	12	300	M 5		1 / 10	11578928
RM/8012/M/670	Mechanical	12	670	M 5		1 / 10	11578934
RM/8016/M/5	Mechanical	16	5	M 5		1 / 10	11578969
RM/8016/M/10	Mechanical	16	10	M 5		1 / 10	11578947
RM/8016/M/15	Mechanical	16	15	M 5		1 / 10	11578951
RM/8016/M/16	Mechanical	16	16	M 5		1 / 10	11578953
RM/8016/M/20	Mechanical	16	20	M 5		1 / 10	11578958
RM/8016/M/25	Mechanical	16	25	M 5		1 / 10	11578960
RM/8016/M/30	Mechanical	16	30	M 5		1 / 10	11578962
RM/8016/M/35	Mechanical	16	35	M 5		1 / 10	11578965
RM/8016/M/40	Mechanical	16	40	M 5		1 / 10	11578967
RM/8016/M/50	Mechanical	16	50	M 5		1 / 10	11578970
RM/8016/M/60	Mechanical	16	60	M 5		1 / 10	11578972
RM/8016/M/70	Mechanical	16	70	M 5		1 / 10	11578973
RM/8016/M/75	Mechanical	16	75	M 5		1 / 10	11578974
RM/8016/M/80	Mechanical	16	80	M 5		1 / 10	11578975
RM/8016/M/90	Mechanical	16	90	M 5		1 / 10	11578976
RM/8016/M/100	Mechanical	16	100	M 5		1 / 10	11578948
RM/8016/M/115	Mechanical	16	115	M 5		1 / 10	11578949
RM/8016/M/125	Mechanical	16	125	M 5		1 / 10	11578950
RM/8016/M/150	Mechanical	16	150	M 5		1 / 10	11578952
RM/8016/M/160	Mechanical	16	160	M 5		1 / 10	11578954
RM/8016/M/175	Mechanical	16	175	M 5		1 / 10	11578955
RM/8016/M/187	Mechanical	16	187	M 5		1 / 10	11578956
RM/8016/M/190	Mechanical	16	190	M 5		1 / 10	11578957
RM/8016/M/200	Mechanical	16	200	M 5		1 / 10	11578959
RM/8016/M/250	Mechanical	16	250	M 5		1 / 10	11578961
RM/8016/M/300	Mechanical	16	300	M 5		1 / 10	11578963
RM/8016/M/310	Mechanical	16	310	M 5		1 / 10	11578964
RM/8016/M/350	Mechanical	16	350	M 5		1 / 10	11578966
RM/8016/M/400	Mechanical	16	400	M 5		1 / 10	11578968
RM/8016/M/550	Mechanical	16	550	M 5		1 / 10	11578971
RM/8020/M/5	Mechanical	20	5		G1/8	1 / 10	11579030
RM/8020/M/10	Mechanical	20	10		G1/8	1 / 10	11579010
RM/8020/M/15	Mechanical	20	15		G1/8	1 / 10	11579015
RM/8020/M/20	Mechanical	20	20		G1/8	1 / 10	11579021
RM/8020/M/25	Mechanical	20	25		G1/8	1 / 10	11579024
RM/8020/M/30	Mechanical	20	30		G1/8	1 / 10	11579026
RM/8020/M/40	Mechanical	20	40		G1/8	1 / 10	11579029
RM/8020/M/65	Mechanical	20	65		G1/8	1 / 10	11579034
RM/8020/M/70	Mechanical	20	70		G1/8	1 / 10	11579035

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Manufacturer ID	Cushioning	Bore diameter	Stroke length	Port Size	Port Size	Operating pressure	Article
		mm	mm	mm	in	bar	
RM/8020/M/80	Mechanical	20	80		G1/8	1 / 10	11579037
RM/8020/M/100	Mechanical	20	100		G1/8	1 / 10	11579011
RM/8020/M/110	Mechanical	20	110		G1/8	1 / 10	11579012
RM/8020/M/120	Mechanical	20	120		G1/8	1 / 10	11579013
RM/8020/M/125	Mechanical	20	125		G1/8	1 / 10	11579014
RM/8020/M/150	Mechanical	20	150		G1/8	1 / 10	11579016
RM/8020/M/160	Mechanical	20	160		G1/8	1 / 10	11579017
RM/8020/M/170	Mechanical	20	170		G1/8	1 / 10	11579018
RM/8020/M/180	Mechanical	20	180		G1/8	1 / 10	11579019
RM/8020/M/185	Mechanical	20	185		G1/8	1 / 10	11579020
RM/8020/M/200	Mechanical	20	200		G1/8	1 / 10	11579022
RM/8020/M/220	Mechanical	20	220		G1/8	1 / 10	11579023
RM/8020/M/250	Mechanical	20	250		G1/8	1 / 10	11579025
RM/8020/M/300	Mechanical	20	300		G1/8	1 / 10	11579027
RM/8020/M/320	Mechanical	20	320		G1/8	1 / 10	11579028
RM/8020/M/500	Mechanical	20	500		G1/8	1 / 10	11579032
RM/8020/M/60	Mechanical	20	600		G1/8	1 / 10	11579033
RM/8020/M/800	Mechanical	20	800		G1/8	1 / 10	11579038
RM/8025/M/5	Mechanical	25	5		G1/8	1 / 10	11579112
RM/8025/M/8	Mechanical	25	8		G1/8	1 / 10	11579121
RM/8025/M/10	Mechanical	25	10		G1/8	1 / 10	11579082
RM/8025/M/12	Mechanical	25	12		G1/8	1 / 10	11579085
RM/8025/M/15	Mechanical	25	15		G1/8	1 / 10	11579091
RM/8025/M/20	Mechanical	25	20		G1/8	1 / 10	11579096
RM/8025/M/25	Mechanical	25	25		G1/8	1 / 10	11579100
RM/8025/M/35	Mechanical	25	35		G1/8	1 / 10	11579106
RM/8025/M/40	Mechanical	25	40		G1/8	1 / 10	11579109
RM/8025/M/50	Mechanical	25	50		G1/8	1 / 10	11579113
RM/8025/M/60	Mechanical	25	60		G1/8	1 / 10	11579115
RM/8025/M/70	Mechanical	25	70		G1/8	1 / 10	11579117
RM/8025/M/75	Mechanical	25	75		G1/8	1 / 10	11579120
RM/8025/M/80	Mechanical	25	80		G1/8	1 / 10	11579122
RM/8025/M/85	Mechanical	25	85		G1/8	1 / 10	11579123
RM/8025/L4/100	Mechanical	25	100		G1/8	1 / 10	11579080
RM/8025/M/100	Mechanical	25	100		G1/8	1 / 10	11579083
RM/8025/M/115	Mechanical	25	115		G1/8	1 / 10	11579084
RM/8025/M/120	Mechanical	25	120		G1/8	1 / 10	11579086
RM/8025/M/125	Mechanical	25	125		G1/8	1 / 10	11579087
RM/8025/M/130	Mechanical	25	130		G1/8	1 / 10	11579088
RM/8025/M/135	Mechanical	25	135		G1/8	1 / 10	11579089
RM/8025/M/140	Mechanical	25	140		G1/8	1 / 10	11579090
RM/8025/M/150	Mechanical	25	150		G1/8	1 / 10	11579092
RM/8025/M/160	Mechanical	25	160		G1/8	1 / 10	11579093
RM/8025/M/175	Mechanical	25	175		G1/8	1 / 10	11579094
RM/8025/M/180	Mechanical	25	180		G1/8	1 / 10	11579095
RM/8025/M/200	Mechanical	25	200		G1/8	1 / 10	11579097
RM/8025/M/210	Mechanical	25	210		G1/8	1 / 10	11579098
RM/8025/M/220	Mechanical	25	220		G1/8	1 / 10	11579099
RM/8025/M/250	Mechanical	25	250		G1/8	1 / 10	11579101
RM/8025/M/280	Mechanical	25	280		G1/8	1 / 10	11579102
RM/8025/M/300	Mechanical	25	300		G1/8	1 / 10	11579103
RM/8025/M/320	Mechanical	25	320		G1/8	1 / 10	11579104

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Manufacturer ID	Cushioning	Bore diameter	Stroke length	Port Size	Port Size	Operating pressure	Article
		mm	mm	mm	in	bar	
RM/8025/M/330	Mechanical	25	330		G1/8	1 / 10	11579105
RM/8025/M/350	Mechanical	25	350		G1/8	1 / 10	11579107
RM/8025/M/375	Mechanical	25	375		G1/8	1 / 10	11579108
RM/8025/M/400	Mechanical	25	400		G1/8	1 / 10	11579110
RM/8025/M/450	Mechanical	25	450		G1/8	1 / 10	11579111
RM/8025/M/500	Mechanical	25	500		G1/8	1 / 10	11579114
RM/8025/M/600	Mechanical	25	600		G1/8	1 / 10	11579116
RM/8025/L4/630	Mechanical	25	630		G1/8	1 / 10	11579081
RM/8025/M/700	Mechanical	25	700		G1/8	1 / 10	11579118
RM/8025/M/735	Mechanical	25	735		G1/8	1 / 10	11579119

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.