

NORGREN Roundline cylinder double acting series RM/55401/M



- Clean line design
- Low friction, long life seals
- Standard magnetic piston for full control system versatility
- Non-lube operation

Characteristics

Series: RM/55401/M

Function: Double acting

Magnetic: Yes

Barrel material: Anodised aluminium

Operating temperature: -20 / 80 °C

Manufacturer ID	Cushioning	Bore diameter	Stroke length	Port Size	Operating pressure	Article
		mm	mm	in	bar	
RM/55433/M/10	Adjustable	32	10	G1/8	1 / 10	11578828
RM/55433/M/25	Adjustable	32	25	G1/8	1 / 10	11578837
RM/55433/M/30	Adjustable	32	30	G1/8	1 / 10	11578839
RM/55433/M/40	Adjustable	32	40	G1/8	1 / 10	11578843
RM/55433/M/50	Adjustable	32	50	G1/8	1 / 10	11578845
RM/55433/M/80	Adjustable	32	80	G1/8	1 / 10	11578848
RM/55433/M/90	Adjustable	32	90	G1/8	1 / 10	11578850
RM/55433/M/100	Adjustable	32	100	G1/8	1 / 10	11578829
RM/55433/M/125	Adjustable	32	125	G1/8	1 / 10	11578831
RM/55433/M/160	Adjustable	32	160	G1/8	1 / 10	11578835
RM/55433/M/200	Adjustable	32	200	G1/8	1 / 10	11578836
RM/55433/M/250	Adjustable	32	250	G1/8	1 / 10	11578838
RM/55433/M/300	Adjustable	32	300	G1/8	1 / 10	11578840
RM/55433/M/900	Adjustable	32	900	G1/8	1 / 10	11578851
RM/55441/M/25	Adjustable	40	25	G1/4	1 / 10	11578858
RM/55441/M/40	Adjustable	40	40	G1/4	1 / 10	11611902
RM/55441/M/50	Adjustable	40	50	G1/4	1 / 10	11578864
RM/55441/M/60	Adjustable	40	60	G1/4	1 / 10	11578865
RM/55441/M/80	Adjustable	40	80	G1/4	1 / 10	11611903
RM/55441/M/100	Adjustable	40	100	G1/4	1 / 10	11578852
RM/55441/M/125	Adjustable	40	125	G1/4	1 / 10	11578853
RM/55441/M/160	Adjustable	40	160	G1/4	1 / 10	11578854
RM/55441/M/200	Adjustable	40	200	G1/4	1 / 10	11578856
RM/55441/M/250	Adjustable	40	250	G1/4	1 / 10	11578859
RM/55441/M/300	Adjustable	40	300	G1/4	1 / 10	11578860
RM/55451/M/25	Adjustable	50	25	G1/4	1 / 10	11578873
RM/55451/M/40	Adjustable	50	40	G1/4	1 / 10	11578876
RM/55451/M/50	Adjustable	50	50	G1/4	1 / 10	11578878
RM/55451/M/80	Adjustable	50	80	G1/4	1 / 10	11578879
RM/55451/M/100	Adjustable	50	100	G1/4	1 / 10	11578868
RM/55451/M/125	Adjustable	50	125	G1/4	1 / 10	11578869
RM/55451/M/160	Adjustable	50	160	G1/4	1 / 10	11578870
RM/55451/M/200	Adjustable	50	200	G1/4	1 / 10	11578872
RM/55451/M/250	Adjustable	50	250	G1/4	1 / 10	11578874
RM/55451/M/300	Adjustable	50	300	G1/4	1 / 10	11578875
RM/55464/M/25	Adjustable	63	25	G3/8	1 / 10	11578886
RM/55464/M/50	Adjustable	63	50	G3/8	1 / 10	11578889

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Manufacturer ID	Cushioning	Bore diameter mm	Stroke length mm	Port Size in	Operating pressure bar	Article
RM/55464/M/80	Adjustable	63	80	G3/8	1 / 10	11578891
RM/55464/M/100	Adjustable	63	100	G3/8	1 / 10	11578880
RM/55464/M/125	Adjustable	63	125	G3/8	1 / 10	11578882
RM/55464/M/160	Adjustable	63	160	G3/8	1 / 10	11578883
RM/55464/M/200	Adjustable	63	200	G3/8	1 / 10	11578884
RM/55464/M/300	Adjustable	63	300	G3/8	1 / 10	11578888
RM/55464/M/320	Adjustable	63	320	G3/8	1 / 10	12313571
RM/55481/M/40	Adjustable	80	40	G3/8	1 / 10	11578899
RM/55481/M/100	Adjustable	80	100	G3/8	1 / 10	11578892
RM/55481/M/125	Adjustable	80	125	G3/8	1 / 10	11578893
RM/55411/M/200	Adjustable	100	200	G1/2	1 / 10	11578823

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.