



NORGREN Rodless cylinder Lintra® Plus double acting magnetic piston series M/146100/M

- New lightweight design extrusion with universal mounting grooves
- Proved and patented sealing system
- Dust protection as standard
- Interchangeability with series M/46000

Characteristics

Series: Lintra

Type: M/146100

Function: Double acting

Magnetic: Yes

Barrel material: Anodised aluminium

Operating temperature: -30 / 80 °C

Manufacturer ID	Cushioning	Bore diameter	Stroke length	Port Size	Operating pressure	Article
		mm	mm	in	bar	
M/146120/M/550	Adjustable	20	550	G1/8	1 / 8	12381163
M/146125/M/120	Adjustable	25	100	G1/8	1 / 8	24200644
M/146125/M/125	Adjustable	25	125	G1/8	1 / 8	24202355
M/146132/M/1320	Adjustable	32	1.32	G1/4	1 / 8	24212281
M/146132/M/400	Adjustable	32	400	G1/4	1 / 8	12493054
M/146132/M/500	Adjustable	32	500	G1/4	1 / 8	12493056
M/146132/M/700	Adjustable	32	700	G1/4	1 / 8	11573274
M/146140/M/900	Adjustable	40	900	G1/4	1 / 8	12493052
M/146150/M/400	Adjustable	50	400	G3/8	1 / 8	24207910

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.