



NORGREN Rodless cylinder Lintra® Plus double acting magnetic piston series M/146000/M

- New lightweight design extrusion with universal mounting grooves
- Proved and patented sealing system
- Dust protection as standard
- Interchangeability with series M/46000

Characteristics

Series: Lintra

Type: M/146000

Function: Double acting

Magnetic: Yes

Barrel material: Plastic

Operating temperature: -30 / 80 °C

Manufacturer ID	Cushioning	Bore diameter	Stroke length	Port Size	Port Size	Operating pressure	Article
		mm	mm	mm	in	bar	
M/146016/M/125	Adjustable	16	125	M 5		1 / 8	24212279
M/146020/M/2420	Adjustable	20	2.42		G1/8	1 / 8	24212882
M/146032/M/1350	Adjustable	32	1.35		G1/4	1 / 8	24212280
M/146032/M/900	Adjustable	32	900		G1/4	1 / 8	12340294
M/146040/M/1000	Adjustable	40	1		G1/4	1 / 8	24201607
M/146040/M/400	Adjustable	40	400		G1/4	1 / 8	12394112
M/146040/M/700	Adjustable	40	700		G1/4	1 / 8	11573273
M/146050/M/160	Adjustable	50	160		G3/8	1 / 8	12707215
M/146050/M/400	Adjustable	50	400		G3/8	1 / 8	24202615
M/146063/MC/100	Adjustable	63	100		G1/2	1 / 8	24200582

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.