

ERIKS Cylindrical vibration damper TA NR



Characteristics

Type: TA

Material rubber: NR

Size table:

D	H	G	L
mm	mm		mm
10	15	M4	10
20	15	M6	15
20	19	M6	16
20	19	M6	20
25	25	M6	18
30	20	M8	20
40	28	M10	25
40	40	M10	20
50	30	M10	
57	44		20
60	60		25
80	70		35
95	76		45

Hardness rubber	Material metal	Outside diameter	Outside height	Thread size	Article
		mm	mm		
55	Galvanized steel	10	15	M4	10041157
55	Galvanized steel	20	15	M6	10041159
55	Galvanized steel	20	19	M6	10041160
55	Galvanized steel	20	19	M6	10041162
55	Galvanized steel	25	25	M6	10041163
55	Galvanized steel	30	20	M8	10041164
55	Galvanized steel	40	28	M10	10041165
55	Galvanized steel	40	40	M10	10041166
55	Galvanized steel	50	30	M10	10041179
55	Galvanized steel	57	44	M8	10041168
55	Galvanized steel	57	44	M8	10041167
55	Galvanized steel	60	60	M10	10041169
55	Galvanized steel	80	70	M 14	10041170
55	Galvanized steel	95	76	M 16	10041171

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.