

CONTARINI DA Cylinder HM2



Characteristics

Type: HM2

Type (DA/SA): Double acting

Max. operating pressure: 250 bar

Front fixation: Bush

Rear fixation: Bush

Bore mm	Number of extensions	Outer diameter piston rod mm	Stroke mm	Built-in size mm	Oilports	Article
32	1	20	50	190	1/4" BSP	12361200
32	1	20	100	240	1/4" BSP	12361201
32	1	20	150	290	1/4" BSP	12361202
32	1	20	200	340	1/4" BSP	12361213
32	1	20	250	390	1/4" BSP	12361214
32	1	20	300	440	1/4" BSP	12361215
32	1	20	400	540	1/4" BSP	12361216
32	1	20	500	640	1/4" BSP	12361217
40	1	20	100	265	1/4" BSP	12361235
40	1	20	150	315	1/4" BSP	12361236
40	1	20	200	365	1/4" BSP	12361237
40	1	20	250	415	1/4" BSP	12361238
40	1	20	300	465	1/4" BSP	12361239
40	1	20	350	515	1/4" BSP	12361240
40	1	20	400	565	1/4" BSP	12361241
40	1	20	450	615	1/4" BSP	12361242
40	1	20	500	665	1/4" BSP	12361243
40	1	25	100	265	1/4" BSP	12361244
40	1	25	150	315	1/4" BSP	12361245
40	1	25	200	365	1/4" BSP	12361246
40	1	25	250	415	1/4" BSP	12361247
40	1	25	300	465	1/4" BSP	12361248
40	1	25	350	515	1/4" BSP	12361249
40	1	25	400	565	1/4" BSP	12361250
40	1	25	450	615	1/4" BSP	12361251
40	1	25	500	665	1/4" BSP	12361252
40	1	25	550	715	1/4" BSP	12361253
40	1	25	600	765	1/4" BSP	12361254
50	1	25	100	280	3/8" BSP	12361255
50	1	25	150	330	3/8" BSP	12361256
50	1	25	200	380	3/8" BSP	12361257
50	1	25	250	430	3/8" BSP	12361258
50	1	25	300	480	3/8" BSP	12361259
50	1	25	350	530	3/8" BSP	12361260
50	1	25	400	580	3/8" BSP	12361261
50	1	25	450	630	3/8" BSP	12361262
50	1	25	500	680	3/8" BSP	12361263
50	1	25	550	730	3/8" BSP	12361264
50	1	25	600	780	3/8" BSP	12361265
50	1	25	700	880	3/8" BSP	12953467
50	1	25	800	980	3/8" BSP	12361266
50	1	25	1000	1,180	3/8" BSP	12361267

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Bore mm	Number of extensions	Outer diameter piston rod mm	Stroke mm	Built-in size mm	Oilports	Article
50	1	30	100	280	3/8" BSP	12953469
50	1	30	150	330	3/8" BSP	12361268
50	1	30	200	380	3/8" BSP	12361269
50	1	30	250	430	3/8" BSP	12361270
50	1	30	300	480	3/8" BSP	12361271
50	1	30	350	530	3/8" BSP	12361272
50	1	30	400	580	3/8" BSP	12361273
50	1	30	450	630	3/8" BSP	12361274
50	1	30	500	680	3/8" BSP	12361275
50	1	30	550	730	3/8" BSP	12361276
50	1	30	600	780	3/8" BSP	12361277
50	1	30	700	880	3/8" BSP	12361278
50	1	30	800	980	3/8" BSP	12361279
50	1	30	1000	1,180	3/8" BSP	12361280
60	1	30	100	310	3/8" BSP	12361281
60	1	30	150	360	3/8" BSP	12361282
60	1	30	200	410	3/8" BSP	12361283
60	1	30	250	460	3/8" BSP	12361284
60	1	30	300	510	3/8" BSP	12361285
60	1	30	350	560	3/8" BSP	12361286
60	1	30	400	610	3/8" BSP	12361287
60	1	30	450	660	3/8" BSP	12361288
60	1	30	500	710	3/8" BSP	12361289
60	1	30	550	760	3/8" BSP	12361290
60	1	30	600	810	3/8" BSP	12361291
60	1	30	700	910	3/8" BSP	12953468
60	1	30	800	1,010	3/8" BSP	12361292
60	1	30	1000	1,210	3/8" BSP	12361293
60	1	35	100	310	3/8" BSP	12361294
60	1	35	150	360	3/8" BSP	12361295
60	1	35	200	410	3/8" BSP	12361296
60	1	35	250	460	3/8" BSP	12361297
60	1	35	300	510	3/8" BSP	12361298
60	1	35	350	560	3/8" BSP	12361299
60	1	35	400	610	3/8" BSP	12361300
60	1	35	450	660	3/8" BSP	12361301
60	1	35	500	710	3/8" BSP	12361302
60	1	35	550	760	3/8" BSP	12361303
60	1	35	600	810	3/8" BSP	12361304
60	1	35	700	910	3/8" BSP	12953470
60	1	35	800	1,010	3/8" BSP	12361305
60	1	35	1000	1,210	3/8" BSP	12361306
60	1	40	200	410	3/8" BSP	12361307
60	1	40	250	460	3/8" BSP	12361308
60	1	40	300	510	3/8" BSP	12361309
60	1	40	350	560	3/8" BSP	12361310
60	1	40	400	610	3/8" BSP	12361311
60	1	40	450	660	3/8" BSP	12361312
60	1	40	500	710	3/8" BSP	12361313
60	1	40	550	760	3/8" BSP	12361314
60	1	40	600	810	3/8" BSP	12361315
60	1	40	700	910	3/8" BSP	12953471

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Bore mm	Number of extensions	Outer diameter piston rod mm	Stroke mm	Built-in size mm	Oilports	Article
60	1	40	800	1,010	3/8" BSP	12361316
60	1	40	1000	1,210	3/8" BSP	12361317
63	1	40	200	410	3/8" BSP	12361218
63	1	40	250	460	3/8" BSP	12361219
63	1	40	300	510	3/8" BSP	12361220
63	1	40	350	560	3/8" BSP	12361221
63	1	40	400	610	3/8" BSP	12361222
63	1	40	450	660	3/8" BSP	12361223
63	1	40	500	710	3/8" BSP	12361224
63	1	40	550	760	3/8" BSP	12361225
63	1	40	600	810	3/8" BSP	12361226
63	1	40	800	1,010	3/8" BSP	12361227
63	1	40	1000	1,210	3/8" BSP	12361228
70	1	35	100	310	3/8" BSP	12361318
70	1	35	150	360	3/8" BSP	12361319
70	1	35	200	410	3/8" BSP	12361320
70	1	35	250	460	3/8" BSP	12361321
70	1	35	300	510	3/8" BSP	12361322
70	1	35	350	560	3/8" BSP	12361323
70	1	35	400	610	3/8" BSP	12361324
70	1	35	450	660	3/8" BSP	12361325
70	1	35	500	710	3/8" BSP	12361326
70	1	35	550	760	3/8" BSP	12361327
70	1	35	600	810	3/8" BSP	12361328
70	1	35	700	910	3/8" BSP	12953472
70	1	35	800	1,010	3/8" BSP	12361329
70	1	35	1000	1,210	3/8" BSP	12361330
70	1	40	200	410	3/8" BSP	12361331
70	1	40	250	460	3/8" BSP	12361332
70	1	40	300	510	3/8" BSP	12361333
70	1	40	350	560	3/8" BSP	12361334
70	1	40	400	610	3/8" BSP	12361335
70	1	40	450	660	3/8" BSP	12361336
70	1	40	500	710	3/8" BSP	12361337
70	1	40	550	760	3/8" BSP	12361338
70	1	40	600	810	3/8" BSP	12361339
70	1	40	800	1,010	3/8" BSP	12361340
70	1	40	1000	1,210	3/8" BSP	12361341
80	1	40	200	440	BSP female 1/2" BSP	12361342
80	1	40	250	490	BSP female 1/2" BSP	12361343
80	1	40	300	540	BSP female 1/2" BSP	12361344
80	1	40	400	640	BSP female 1/2" BSP	12361346
80	1	40	500	740	BSP female 1/2" BSP	12361347
80	1	40	600	840	BSP female 1/2" BSP	12361348
80	1	40	700	940	BSP female 1/2" BSP	12953473
80	1	40	800	1,040	BSP female 1/2" BSP	12361349
80	1	40	1000	1,240	BSP female 1/2" BSP	12361350
80	1	50	200	440	BSP female 1/2" BSP	12361351
80	1	50	250	490	BSP female 1/2" BSP	12361352
80	1	50	300	540	BSP female 1/2" BSP	12361353
80	1	50	400	640	BSP female 1/2" BSP	12361354
80	1	50	500	740	BSP female 1/2" BSP	12361355

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Bore mm	Number of extensions	Outer diameter piston rod mm	Stroke mm	Built-in size mm	Oilports	Article
80	1	50	600	840	BSP female 1/2" BSP	12361356
80	1	50	700	940	BSP female 1/2" BSP	12953474
80	1	50	800	1,040	BSP female 1/2" BSP	12361357
80	1	50	1000	1,240	BSP female 1/2" BSP	12361358
90	1	50	300	556	BSP female 1/2" BSP	12361229
90	1	50	400	656	BSP female 1/2" BSP	12361230
90	1	50	500	756	BSP female 1/2" BSP	12361231
90	1	50	600	856	BSP female 1/2" BSP	12361232
90	1	50	700	956	BSP female 1/2" BSP	12953475
90	1	50	800	1,056	BSP female 1/2" BSP	12361233
90	1	50	1000	1,256	BSP female 1/2" BSP	12361234
100	1	50	200	480	BSP female 1/2" BSP	12361359
100	1	50	250	530	BSP female 1/2" BSP	12361360
100	1	50	300	580	BSP female 1/2" BSP	12361361
100	1	50	400	680	BSP female 1/2" BSP	12361362
100	1	50	500	780	BSP female 1/2" BSP	12361363
100	1	50	600	880	BSP female 1/2" BSP	12361364
100	1	50	700	980	BSP female 1/2" BSP	12953476
100	1	50	800	1,080	BSP female 1/2" BSP	12361365
100	1	50	1000	1,280	BSP female 1/2" BSP	12361366
100	1	60	300	580	BSP female 1/2" BSP	12361367
100	1	60	400	680	BSP female 1/2" BSP	12361368
100	1	60	500	780	BSP female 1/2" BSP	12361369
100	1	60	600	880	BSP female 1/2" BSP	12361370
100	1	60	700	980	BSP female 1/2" BSP	12953477
100	1	60	800	1,080	BSP female 1/2" BSP	12361371
100	1	60	1000	1,280	BSP female 1/2" BSP	12361372

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.