

CONTARINI DA Cylinder HFR2S



Characteristics

Type: HFR2S

Type (DA/SA): Double acting

Max. operating pressure: 250 bar

Front fixation: Bush

Rear fixation: Bored endplug

Bore mm	Number of extensions	Outer diameter piston rod mm	Stroke mm	Built-in size mm	Oilports	Article
25	1	16	50	160	1/4" BSP	12360431
25	1	16	100	210	1/4" BSP	12360695
25	1	16	150	260	1/4" BSP	12360696
25	1	16	200	310	1/4" BSP	12360697
32	1	20	50	205	1/4" BSP	12360698
32	1	20	100	255	1/4" BSP	12360699
32	1	20	150	305	1/4" BSP	12360700
32	1	20	250	405	1/4" BSP	12360702
32	1	20	300	455	1/4" BSP	12360703
32	1	20	400	555	1/4" BSP	12360704
32	1	20	500	655	1/4" BSP	12360701
32	1	20	500	655	1/4" BSP	12360705
32	1	20	600	755	1/4" BSP	12953443
32	1	20	700	855	3/8" BSP	12953444
40	1	25	100	270	3/8" BSP	12360706
40	1	25	150	320	3/8" BSP	12360707
40	1	25	200	370	3/8" BSP	12360708
40	1	25	250	420	3/8" BSP	12360709
40	1	25	300	470	3/8" BSP	12360710
40	1	25	400	570	3/8" BSP	12360711
40	1	25	500	670	3/8" BSP	12360712
40	1	25	600	770	3/8" BSP	12360713
40	1	25	700	870	3/8" BSP	12360714
40	1	25	800	970	3/8" BSP	12360715
40	1	25	1000	1,170	3/8" BSP	12953445
50	1	30	100	300	3/8" BSP	12360716
50	1	30	150	350	3/8" BSP	12360717
50	1	30	200	400	3/8" BSP	12360718
50	1	30	250	450	3/8" BSP	12360719
50	1	30	300	500	3/8" BSP	12360720
50	1	30	400	600	3/8" BSP	12360721
50	1	30	500	700	3/8" BSP	12360722
50	1	30	600	800	3/8" BSP	12360723
50	1	30	700	900	3/8" BSP	12360724
50	1	30	800	1,000	3/8" BSP	12360725
50	1	30	900	1,100	3/8" BSP	12360726
50	1	30	1000	1,200	3/8" BSP	12360727
60	1	30	100	300	3/8" BSP	12360728
60	1	30	150	350	3/8" BSP	12360729
60	1	30	200	400	3/8" BSP	12360730
60	1	30	250	450	3/8" BSP	12360731
60	1	30	300	500	3/8" BSP	12360732

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Bore mm	Number of extensions	Outer diameter piston rod mm	Stroke mm	Built-in size mm	Oilports	Article
60	1	30	350	550	3/8" BSP	12360733
60	1	30	400	600	3/8" BSP	12360734
60	1	30	450	650	3/8" BSP	12360735
60	1	30	500	700	3/8" BSP	12360736
60	1	30	600	800	3/8" BSP	12360737
60	1	30	700	900	3/8" BSP	12360738
60	1	35	100	300	3/8" BSP	12953446
60	1	35	150	350	3/8" BSP	12953447
60	1	35	200	400	3/8" BSP	12360739
60	1	35	250	450	3/8" BSP	12953448
60	1	35	300	500	3/8" BSP	12360740
60	1	35	350	550	3/8" BSP	12953449
60	1	35	400	600	3/8" BSP	12360741
60	1	35	450	650	3/8" BSP	12953450
60	1	35	500	700	3/8" BSP	12360742
60	1	35	600	800	3/8" BSP	12360743
60	1	35	700	900	3/8" BSP	12360744
60	1	35	800	1,000	3/8" BSP	12360745
60	1	35	900	1,100	3/8" BSP	12360746
60	1	35	1000	1,200	3/8" BSP	12360747
70	1	40	200	410	3/8" BSP	12360748
70	1	40	250	460	3/8" BSP	12360749
70	1	40	300	510	3/8" BSP	12360750
70	1	40	350	560	3/8" BSP	12360751
70	1	40	400	610	3/8" BSP	12360752
70	1	40	450	660	3/8" BSP	12360753
70	1	40	500	710	3/8" BSP	12360754
70	1	40	600	810	3/8" BSP	12360755
70	1	40	700	910	3/8" BSP	12360756
70	1	40	800	1,010	3/8" BSP	12360757
70	1	40	900	1,110	3/8" BSP	12360758
70	1	40	1000	1,210	3/8" BSP	12953451
80	1	40	200	410	3/8" BSP	12360759
80	1	40	250	460	3/8" BSP	12360760
80	1	40	300	510	3/8" BSP	12360761
80	1	40	350	560	3/8" BSP	12360762
80	1	40	400	610	3/8" BSP	12360763
80	1	40	500	710	3/8" BSP	12360764
80	1	40	600	810	3/8" BSP	12360765
80	1	40	700	910	3/8" BSP	12360766
80	1	40	800	1,010	3/8" BSP	12360767
80	1	40	900	1,110	3/8" BSP	12360768
80	1	40	1000	1,210	3/8" BSP	12360769
100	1	50	200	425	BSP female 1/2" BSP	12360770
100	1	50	300	525	BSP female 1/2" BSP	12360771
100	1	50	400	625	BSP female 1/2" BSP	12360772
100	1	50	500	725	BSP female 1/2" BSP	12360773
100	1	50	700	925	BSP female 1/2" BSP	12360774
100	1	50	900	1,125	BSP female 1/2" BSP	12360775
100	1	50	1000	1,225	BSP female 1/2" BSP	12360776

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.