Support roller stand, series 90000, with suspended axle

Standard variation of carrier rollers, series 90000, installation length 200 mm



ML

TAAAAAA

0¢

• Motorised roller guides and conical carrier rollers as well as special designs with stainless steel bearings are also available on request.

Series 90000 carrier rollers can be produced in almost all required lengths.

Carrier rollers - standard versions

The carrier rollers illustrated here are only a small selection from the production range. Other designs on request.

Required order information:

- Installation length EL (clearance between fames)
- Roll diameter Ø D
- Roller material
 - Axis dimension Ø d and axis design
 - Required load capacity

IG 8

.

Inner thread Ø 12 mm IG M8 IG 12 Inner thread Ø 20 mm IG M12 FA = spring axis

* The load capacity depends on the installation length, axis and type of load. The stated values relate to the bearing assembly.

Load capacity up to 20 kg

Gravity roll with plastic roll base for roller guides,

Continuous flow racks and where ever light conveyor materials are moved.

Plastic roller coating, ball bearing, very smooth.

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Page 1/1



Т