


BAUER Crane arm for forklift trucks, painted



Telescopic loader, RAL 2000

- To extend the reach of the forklift**


Stable steel construction, optional rigid or height-adjustable/tilting load arms, interior arm extendable and securable with locking pins in the extended position.

- Durable and safe**

Chain security against unintended slipping. 1 or 2 swivel hooks Forklift sleeves for forks, interior: WxH 184x84 mm.


- Surface**

Painted RAL 2000 orange or galvanised, other colours on request (see variety).



- Telescopic arm 8 x extendable

- 2 swivel hooks



Type	Position	1	2	3	4	5	6	7	8	9
10	11	12	13	14	Weight					
Distance (mm)		710	1000	1290	1590	1870	2055	2255		
2455	2655	2855	3055	3255	3455	3655	3855	4055		
(kg)										
rigid 2.5	Load capacity (kg)			2500	2500	2500	1800	1400		
1200	1050	950	850	770	700	650	600	560		
175	Load capacity (kg)			5000	3550	2750	2250	1950		
1700	1550	1400	1300	1200	1150	1050	1000			
950	195									
Distance (mm)		695	990	1285	1580	1825	2090	2290		
2490	2690	2890	3090	3290	3490	3690	3890	4090		
height adjustable 2.5	Load capacity (kg)			2500	2500	2500	2500	1800		
1400	1200	1050	950	850	770	700	650			
600	560	218								
height adjustable 5.0	Load capacity (kg)			5000	3550	2750	2250	1950		
1950	1700	1550	1400	1300	1200	1150	1050			
1000	950	250								

Please observe load capacity of forklift!

Illustration does not correspond to colour to be ordered. These and further colours without surcharge, see colour pictograms.

Description	Article
Telescopic loader KT 2.5 I	12965649
Telescopic loader KTH 2.5 I	12965651

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.