

DANFOSS Orbitmotor 10K (10000) Series



Characteristics

Series: 10K (10000)

Direction of rotation: Clockwise and counterclockwise

Mounting flange	Drive shaft	Displacement cm³/r	Max. operating pressure bar	Inlet port	Outlet port	Position oil ports	Code	Article
SAE-C 4 bolts	Cylindrical 2.1/4" [57,1 mm]	345	205	1.5/16-12 UNF female	1.5/16-12 UNF female	Side	119-1028	1010026
SAE-C 4 bolts	Cylindrical 2.1/4" [57,1 mm]	480	205	1.5/16-12 UNF female	1.5/16-12 UNF female	Side	119-1029	1010027
SAE-C 4 bolts	Cylindrical 2.1/4" [57,1 mm]	665	205	1.5/16-12 UNF female	1.5/16-12 UNF female	Side	119-1030	1010028
SAE-C 4 bolts	Cylindrical 2.1/4" [57,1 mm]	940	190	SAE 3000 psi 1.1/4" SAE 3000 psi 1.1/4"		Side	119-1043	923613
SAE-C 4 bolts	Cylindrical 2.1/4" [57,1 mm]	940	190	1.5/16-12 UNF female	1.5/16-12 UNF female	Side	119-1031	1010000
SAE-C 4 bolts	Spline 16 teeth 8/16	940	190	1.5/16-12 UNF female	1.5/16-12 UNF female	Side	119-1035	1064343

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.