


FORMAT ISO boring bar 95° A.-SDUCR/L with internal cooling type 2969



Design: Boring bar for inserts 7° positive, screw clamping, tool carrier nickel-plated.

Supplied in sets of 3 without inserts, without screwdriver.

Application: Boring.



Description	Article
Boring bar 93deg. internal cooling A10H SDUCL 07	12050882
Boring bar 93deg. internal cooling A10H SDUCR 07	12050881
Boring bar 93deg. internal cooling A12K SDUCL 07	12050884
Boring bar 93deg. internal cooling A12K SDUCR 07	12050883
Boring bar 93deg. internal cooling A16M SDUCL 07	12050886
Boring bar 93deg. internal cooling A16M SDUCR 07	12050885
Boring bar 93deg. internal cooling A20Q SDUCL 11	12050888
Boring bar 93deg. internal cooling A20Q SDUCR 11	12050887
Boring bar 93deg. internal cooling A25Q SDUCL 11	12050890
Boring bar 93deg. internal cooling A25Q SDUCR 11	12050889

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.