



SKF High precision axial contact thrust bearing Series: BTW

Characteristics

Series: BTW

Cage: PA66, glass fiber reinforced

Variant: Double direction

Application

- Recommended in: Chemical

Manufacturer ID	Inner diameter mm	Outer diameter mm	Height mm	Contact angle °	With sealing	Article
BTW 35 CTN9/SP	35	62	34	60	No	13199578
BTW 40 CTN9/UP	40	68	36	60	No	13199579
BTW 40 CTN9/SP	40	68	36	60	No	23756288
BTW 50 CATN9/SP	52	80	38	60	No	13199580
BTW 55 CTN9/SP	55	90	44	60	No	13199581
BTW 60 CTN9/SP	60	95	44	60	No	13199582
BTW 45 CTN9/SP	90	150	76	60	No	23756289
BTW 95 CTN9/SP	95	145	60	60	No	13199583
BTW 50 CTN9/SP	100	160	76	60	No	23756290
BTW 110 CTN9/SP	110	170	72	60	No	12716322
BTW 55 CATN9/SP	114	180	88	60	No	24002120
BTW 120 CTN9/SP	120	180	72	60	No	13199574
BTW 130 CTN9/SP	130	200	84	60	No	12987593
BTW 65 CTN9/SP	130	200	88	60	No	24002111
BTW 70 CTN9/SP	140	220	96	60	No	23756294
BTW 75 CTN9/SP	150	230	96	60	No	12121514
BTW 80 CTN9/SP	160	250	108	60	No	23756297
BTW 80 CATN9/SP	166	250	108	60	No	12121515
BTW 85 CTN9/SP	170	260	108	60	No	23756299
BTW 90 CTN9/SP	180	280	120	60	No	24002113
BTW 90 CATN9/SP	186	280	120	60	No	12121518
BTW 100 CTN9/SP	200	300	120	60	No	12121505

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.