



SKF Straight bushing Requiring maintenance Phosphor-Zinnbronze (CuSn10P)/Phosphor-Zinnbronze (CuSn10P) Series: PBM

- Solid bronze bushings can be lubricated with either oil or grease. The lubricant not only improves the sliding properties, but also reduces wear and prevents corrosion.

Advantages of solid bronze bushings include:

- insensitive to dirty environments
- resistant to shock loads and vibrations at low speed
- good resistance to corrosive contaminants
- equipped with grooves to retain lubricants

- Applications include:
- construction machinery
- transport equipment
- pulp and papermaking machinery
- offshore equipment

Characteristics

Series: PBM

With collar: No

Maintenance: Requiring maintenance

Tread material: Phosphor-Zinnbronze [CuSn10P]

Manufacturer ID	Shaft diameter mm	Outer diameter mm	Width mm	Article
PBM 202820 M1G1	20	28	20	23768522
PBM 202830 M1G1	20	28	30	23768523
PBM 253525 M1G1	25	35	25	23768524
PBM 253535 M1G1	25	35	35	23768525
PBM 304030 M1G1	30	40	30	23768526
PBM 304045 M1G1	30	40	45	23768527
PBM 354535 M1G1	35	45	35	23768528
PBM 354550 M1G1	35	45	50	23768529
PBM 404840 M1G1	40	48	40	23768530
PBM 405060 M1G1	40	50	60	23768532
PBM 506050 M1G1	50	60	50	23768537
PBM 607060 M1G1	60	70	60	23768541
PBM 607560 M1G1	60	75	60	23768542
PBM 708560 M1G1	70	85	60	23768546
PBM 809570 M1G1	80	95	70	23768550
PBM 10012080 M1G1	100	120	80	23768521
PBM 100120120 M1G1	100	120	120	23768520

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.