



SKF V-ring seals for SNL & SE-series bearing housings series TSN..A

- V-ring seals consist of a V-ring and a sheet steel sealing washer with a vulcanized rubber lip. The rubber lip fits into the seal groove in the housing. The washer is protected against corrosion. V-rings can accommodate circumferential speeds up to 7 m/s. For circumferential speeds between 7 and 12 m/s, they should be located axially on the shaft. At speeds above 12 m/s, a support ring must be used to prevent the seal from lifting. Seals per pack: 2
- Material: nitrile rubber, steel
- Temperature range: -40°C to +100°C
- Max. circumferential speed: 7 m/s, 12 m/s for special conditions

Characteristics

Series: TSN..A

Material: NBR/steel

Operating temperature: -40 / 100 °C

Manufacturer ID	Inner diameter mm	Outer diameter mm	Width mm	Article
TSN 505 A	20	41.5	4.8	23221573
TSN 605 A	20	46.5	4.8	23221636
TSN 506 A	25	46.5	4.8	23221576
TSN 606 A	25	56.5	4.8	23221639
TSN 507 A	30	56.5	4.8	23221580
TSN 607 A	30	61.5	4.8	23221642
TSN 206 A	31	39	7.5	23770748
TSN 306 A	35	56.5	4.8	23770790
TSN 508 A	35	61.5	4.8	23221586
TSN 608 A	35	72.5	4.8	23221645
TSN 207 A	40	50	9	23770750
TSN 509 AE	40	66.5	4.8	23221591
TSN 509 A	40	66.5	4.8	23221590
TSN 609 A	40	77.5	4.8	1066175
TSN 307 A	45	66.5	4.8	23770792
TSN 510 A	45	72.5	4.8	1066147
TSN 610 A	45	82.5	4.8	23221649
TSN 209 A	49	59	9	24004588
TSN 208 A	50	55	9	23770752
TSN 308 A	50	72.5	4.8	23770794
TSN 511 A	50	77.5	4.8	1066176
TSN 611 A	50	87.5	4.8	23221651
TSN 210 A	54	64	9	23770755
TSN 309 A	55	77.5	4.8	23770796
TSN 512 A	55	82.5	4.8	23221597
TSN 612 A	55	97.5	4.8	1066488
TSN 211 A	58	68	9	24004590
TSN 310 A	60	82.5	4.8	23770798
TSN 513 A	60	87.5	4.8	1066033
TSN 613 A	60	103	4.8	23221655
TSN 212 A	63	75	11	23770757
TSN 515 A	65	97.5	4.8	23221602

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Manufacturer ID	Inner diameter	Outer diameter	Width	Article
	mm	mm	mm	
TSN 615 A	65	113	4.8	23221657
TSN 213 A	67	79	11	23770759
TSN 516 A	70	103	4.8	23221605
TSN 616 A	70	144	5.8	23221660
TSN 313 A	75	103	4.8	23770806
TSN 517 A	75	108	4.8	23221607
TSN 617 A	75	150.5	5.8	23221664
TSN 215 A	76	88	11	24004593
TSN 314 A	80	108	4.8	23770808
TSN 518 A	80	113	4.8	23221609
TSN 315 A	85	113	4.8	23770810
TSN 519 A	85	144	5.8	23221612
TSN 619 A	85	160.5	5.8	23221667
TSN 216 A	90	118.5	4.8	23770762
TSN 316 A	90	144	5.8	23770812
TSN 520 A	90	150.5	5.8	23221615
TSN 620 A	90	170.5	5.8	23770958
TSN 217 A	95	122.5	4.8	23770765
TSN 317 A	95	150.5	5.8	23770815
TSN 218 A	100	130.5	4.8	23770768
TSN 522 A	100	160.5	5.8	23221617
TSN 319 A	110	160.5	5.8	23770817
TSN 524 A	110	170.5	5.8	23221620
TSN 220 A	115	150.5	5.8	23770772
TSN 320 A	115	170.5	5.8	23770818
TSN 526 A	115	180.5	5.8	23770894
TSN 222 A	125	160.5	5.8	23770775
TSN 528 A	125	190.5	5.8	23221627
TSN 224 A	135	170.5	5.8	23770778
TSN 530 A	135	205.5	5.8	23770902
TSN 532 A	140	215.5	5.8	23221633
TSN 226 A	145	180.5	5.8	23770781
TSN 228 A	155	190.5	5.8	23770783
TSN 230 A	165	205.5	5.8	23770785
TSN 232 A	175	215.5	5.8	23770787

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.