



## EWELLIX Combined linear bushing/deep groove ball bearing Closed Series: LPAR

Linear plain bearings have the same external dimensions as LBC linear ball bearings and provide smooth, stick-slip-free operation. They are made from POM with a special polyethylene. These linear plain bearings are self-lubricating under normal conditions and require minimal maintenance.

### Type LPAR

Standard linear plain bearing (ISO series 3) available diameter from 5 to 80 mm, with fixation holes and grooves. These variants, without shields or seals, can be relubricated except for LPAR 5 and 8. Bearings without a grease fitting should be held in place by a retaining ring (according to DIN 471) on either side of the bearing. Bearings with a grease fitting can be fixed via the grease fitting.

### Characteristics

**Series:** LPAR

**Model:** Closed

**With sealing:** No

Manufacturer ID	Shaft diameter mm	Outer diameter mm	Length mm	Article
LPAR 5	5	12	22	24024922
LPAR 8	8	16	25	24024925
LPAR 12	12	22	32	24024921
LPAR 16	16	26	36	23773126
LPAR 20	20	32	45	23773127
LPAR 25	25	40	58	23773128
LPAR 30	30	47	68	23773129
LPAR 40	40	62	80	23773130
LPAR 50	50	75	100	24024923
LPAR 60	60	90	125	24024924
LPAR 80	80	120	165	24024926

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.