

SKF Thrust washer Series: AS

- AS series thin universal washersare 1 mm thick
- are made of spring steel and hardened
- can be used as shaft or housing washers for needle roller thrust bearings in the AXK series
- can be used as shaft washers for bearings in the AXW series
- are available for $4 \le d \le 160 \text{ mm}$

Can be used to provide a cost-effective bearing solution, if adjacent machine components are not hardened, but have adequate stiffness and the requirements to geometrical tolerances are moderate. Both faces of the washers are polished and can be used as raceways.

Characteristics

Series: AS

Manufacturer ID	Inner diameter	Outer diameter	Width	Article
	mm	mm	mm	
AS 0619	6	19	1	23760094
AS 0821	8	21	1	23760095
AS 1024	10	24	1	23760097
AS 1226	12	26	1	23760100
AS 1528	15	28	1	23760101
AS 1730	17	30	1	23760102
AS 2035	20	35	1	23760103
AS 2542	25	42	1	23760104
AS 3047	30	47	1	23760105
AS 3552	35	52	1	23760106
AS 4060	40	60	1	23760107
AS 4565	45	65	1	23760108
AS 5070	50	70	1	23760109
AS 5578	55	78	1	23760110
AS 6085	60	85	1	23760111
AS 6590	65	90	1	24003069
AS 7095	70	95	1	23760112
AS 75100	75	100	1	24003070
AS 85110	85	110	1	23760114
AS 90120	90	120	1	23760115
AS 100135	100	135	1	23760096
AS 110145	110	145	1	23760098
AS 120155	120	155	1	23760099
AS 130170	130	170	1	24003068
AS 140180	140	180	1	12014187
AS 160200	160	200	1	24045065

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Page 1/1

ERIKS