

STAUFF Test coupling bulkhead for fluid media SSK-20

Test couplings with ball valve from the Stauff Test 20 series with connection thread M16x2 according to ISO 15171-2

Characteristics

Series: SSK-20 Adaption thread: M 16x2 Coupling material: Steel, galvanized Surface protection: Zinc-Nickel

Application


- Monitoring and control of pressure
- Sampling in high- and low-pressure systems
- Venting
- Suitable for hydraulic oils and other Mineral oil based fluids [Check compatibility of seal material]


Technical Information

- Standard material: Steel, zinc/nickel-plated = W3
- Optional: stainless steel V2A (W4) and V4A (W5)
- Max. working pressure 630 bar
- Connection under pressure up to max. 400 bar
- Internal sealings made of FKM (Viton®)
- Ball: Stainless Steel

Execution

- Test coupling bulkhead version
- Test system at working pressure
- Leakproof connection before piston valve is open
- Simple connection to measurement, control and switching devices
- Self locking metal protective cap





Size table:

h	SW	Т
mm	mm	
72	19	M14x1.5
72	22	M16x1.5
72	24	M18x1.5
72	19	M16x2

Version A

Connection type	Connection size	Model	Sealing	Protection cap	Article
Cutting ring connection	8L - M14x1.5	В		Metal knurled protection cap	11359419

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Т

Page 1/2

Т



Pressure test points | Test points

Connection type	Connection size	Model	Sealing	Protection cap	Article
Cutting ring connection	8S - M16x1.5	В		Metal knurled protection cap	978426
Cutting ring connection	8S - M16x1.5	В	FKM (FPM)	Metal knurled protection cap	11360476
Cutting ring connection	10S - M18x1.5	В		Metal knurled protection cap	11360701
Cutting ring connection	12L - M18x1.5	В		Metal knurled protection cap	11360105
External thread	M 16x2	А		Metal knurled protection cap	11359421
External thread	M 16x2	А	NBR	Metal knurled protection cap	11359552

e or e advice. Page 2/2 PR_RC0202_0019_PB_EN_17.05.2024 Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

