

STAUFF Test hose SGS Test 20 (M16x2) x Test 20 (M16x2)



Characteristics

- Coupling material:** Steel
- Surface protection:** Zinc-Nickel
- Connection type connection 1:** Test 20
- Connection type connection 2:** Test 20
- Reinforcement type:** Synthetic fibre
- Tube material:** PA
- Cover material:** PA
- Cover colour:** Black
- Medium temperature (continuous):** -35 / 100 °C

Hose ID (DN)	Outside diameter	Maximum operating pressure	Bending radius	Size of threaded connection 1	Size of threaded connection 2	Length	Minimum burst pressure	Test pressure	Article
	mm	bar	mm			mm	bar	bar	
DN04	8.6	340	40	M 16x2	M 16x2	400	850	570	11360400
DN04	8.6	340	40	M 16x2	M 16x2	630	850	570	11360131
DN04	8.6	340	40	M 16x2	M 16x2	1000	850	570	11360078
DN04	8.6	340	40	M 16x2	M 16x2	1500	850	570	11360155
DN04	8.6	340	40	M 16x2	M 16x2	1700	850	570	11361475
DN04	8.6	340	40	M 16x2	M 16x2	2000	850	570	11359511
DN04	8.6	340	40	M 16x2	M 16x2	2500	850	570	11359802
DN04	8.6	340	40	M 16x2	M 16x2	5000	850	570	11361280

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.