



STAUFF Test hose SMS Test 15 (M16x1.5) x Standpipe connection DKO

Characteristics

- Coupling material:** Steel
- Surface protection:** Zinc-Nickel Black
- Connection type connection 1:** Test 15
- Connection type connection 2:** Standpipe connection DKO
- Reinforcement type:** Synthetic fibre
- Tube material:** PA
- Cover material:** PA
- Cover colour:** Black
- Medium temperature (continuous):** -35 / 100 °C

Hose ID (DN)	Outside diameter	Maximum operating pressure	Bending radius	Size of threaded connection 1	Size of threaded connection 2	Length	Minimum burst pressure	Test pressure	Article
	mm	bar	mm			mm	bar	bar	
DN02	5	400	20	M 16x1.5	8L - M14x1.5	260	1100	600	11360069
DN02	5	400	20	M 16x1.5	8L - M14x1.5	1800	1100	600	11360296
DN02	5	400	20	M 16x1.5	10L - M16x1.5	450	1100	600	11360065
DN02	5	400	20	M 16x1.5	10L - M16x1.5	800	1100	600	11360650
DN02	5	630	20	M 16x1.5	6S - M14x1.5	250	1900	950	11360066
DN02	5	630	20	M 16x1.5	6S - M14x1.5	370	1900	950	11360067

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.