



STAUFF Test hose SMS Test 15 (M16x1.5) x Test 15 (M16x1.5) 90° elbow short wire

Characteristics

- Coupling material:** Steel
- Surface protection:** Zinc-Nickel Black
- Connection type connection 1:** Test 15
- Connection type connection 2:** Test 15 90° elbow short
- Reinforcement type:** Synthetic fibre
- Tube material:** PA
- Cover material:** PA
- Cover colour:** Black
- Medium temperature (continuous):** -35 / 100 °C

Hose ID (DN)	Outside diameter	Maximum operating pressure	Bending radius	Size of threaded connection 1	Size of threaded connection 2	Length	Minimum burst pressure	Test pressure	Article
	mm	bar	mm			mm	bar	bar	
DN02	5	630	20	M 16x1.5	M 16x1.5	450	1900	950	11361535
DN02	5	630	20	M 16x1.5	M 16x1.5	800	1900	950	11361536
DN02	5	630	20	M 16x1.5	M 16x1.5	1100	1900	950	11361537
DN02	5	630	20	M 16x1.5	M 16x1.5	1500	1900	950	11361538
DN02	5	630	20	M 16x1.5	M 16x1.5	1800	1900	950	11361539
DN02	5	630	20	M 16x1.5	M 16x1.5	1900	1900	950	11361540
DN02	5	630	20	M 16x1.5	M 16x1.5	2100	1900	950	11361541

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.