

STAUFF Test hose SMS BSPP-fs x BSPP-fs



Characteristics

- Coupling material:** Steel
- Surface protection:** Zinc-Nickel
- Connection type connection 1:** Female swivel thread
- Connection type connection 2:** Female swivel thread
- Reinforcement type:** Synthetic fibre
- Tube material:** PA
- Cover material:** PA
- Cover colour:** Black
- Medium temperature (continuous):** -35 / 100 °C

Hose ID (DN)	Outside diameter	Maximum operating pressure	Bending radius	Size of threaded connection 1	Size of threaded connection 2	Length	Minimum burst pressure	Test pressure	Article
	mm	bar	mm			mm	bar	bar	
DN02	5	400	20	1/4" BSP cyl.	1/4" BSP cyl.	1000	1100	600	11360695
DN04	8.6	340	40	1/4" BSP cyl.	1/4" BSP cyl.	4000	850	570	11359932
DN04	8.6	340	40	1/4" BSP cyl.	1/4" BSP cyl.	7000	850	570	11360768

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.