



SKF Single-Point automatic lubricator series LAGD

- The units are supplied ready-to-use straight from the box and filled with a wide range of high performance SKF lubricants. Tool-free activation and time-setting allow easy and accurate adjustment of lubrication flow. Flexible dispense rate from 1 to 12 months
- Stoppable or adjustable if required
- Intrinsic safety rating: ATEX approved for zone 0
- Transparent lubricant container allows visual inspection of dispense rate
- Compact size, permits installation in restrictive areas
- Greases and chain oils available



Typical applications

- Applications in restrictive and hazardous locations
- Bearing housing lubrication
- Electric motors
- Fans and pumps
- Conveyors
- Cranes
- Chains (oil)
- Elevators and escalators (oil)

Characteristics

Series: LAGD

Type: LAGD 125/FG2

Drive mechanism	Container volume ml	Lubricant	Article
			14012801
Gass cell	60	Empty	23766517
Gass cell	60	LGEM 2	23766513
Gass cell	60	LGHB 2	23766514
Gass cell	60	LGHQ 2	14066219
Gass cell	60	LGWA 2	23766518
Gass cell	60	LHMT 68	23766515
Gass cell	125	Empty	23766501
Gass cell	125	LFFM 100	14202894
Gass cell	125	LGEM 2	23766497
Gass cell	125	LGFG 2	14464408
Gass cell	125	LGFP 2	23766498
Gass cell	125	LGGB 2	23766502
Gass cell	125	LGHB 2	23766503
Gass cell	125	LGWA 2	23766508
Gass cell	125	LGWM 2	12174618
Gass cell	125	LHMT 68	23766505

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.