



FLEXION Straight adapter stainless steel 316Ti BSPP-m/BSPP-m Q-STR-BM60-BM60

- Straight adapter
- BSPP male thread both sides with 60° cone
- Metallic sealing edge Form B
- Material: stainless steel 316Ti

Characteristics

Series: Q-STR-BM60-BM60

Shape: Straight

Material: Stainless steel 316 Ti [1.4571]

Dash	T1	T2	D1 [mm]	D2 [mm]	L1 [mm]	i1 [mm]	i2 [mm]	S1 [mm]	Weight [g]
-2-2	1/8"	1/8"	4	4	24	8	8	14	15.6
-4-2	1/4"	1/8"	5	4	28	11	8	19	29.09
-4-4	1/4"	1/4"	5	5	32	11	11	19	36.5
-6-2	3/8"	1/8"	8	4	30	12	8	22	42.96
-6-4	3/8"	1/4"	8	5	33	12	11	22	47.66
-6-6	3/8"	3/8"	8	8	35	12	12	22	54.54
-8-4	1/2"	1/4"	11	5	37	14	11	27	77.22
-8-6	1/2"	3/8"	11	8	38.5	14	12	27	82.41
-8-8	1/2"	1/2"	11	11	41	14	14	27	91.61
-10-6	5/8"	3/8"	14	8	42	16	12	30	106.71
-10-8	5/8"	1/2"	14	11	44	16	14	30	113.04
-10-10	5/8"	5/8"	14	14	45	16	16	30	109.97
-12-6	3/4"	3/8"	17	8	41.5	16	12	32	119.3
-12-8	3/4"	1/2"	17	11	44	16	14	32	128.67
-12-10	3/4"	5/8"	17	14	46	16	16	32	131.09
-12-12	3/4"	3/4"	17	17	46	16	16	32	132.97
-16-6	1"	3/8"	22	8	47	19	12	41	213.86
-16-8	1"	1/2"	22	11	48	19	14	41	207.08
-16-12	1"	3/4"	22	17	50	19	16	41	211.9
-16-16	1"	1"	22	22	53	19	19	41	229.73
-20-12	1.1/4"	3/4"	29	17	54	20	16	50	351.03
-20-16	1.1/4"	1"	29	22	57	20	19	50	367.79
-20-20	1.1/4"	1.1/4"	29	29	57	20	20	50	367.86
-24-12	1.1/2"	3/4"	33	17	56	22	16	55	439.43
-24-16	1.1/2"	1"	33	22	60	22	19	55	475.09
-24-20	1.1/2"	1.1/4"	33	29	60	22	20	55	472.07
-24-24	1.1/2"	1.1/2"	33	33	62	22	22	55	496.63

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Dash	T1	T2	D1 [mm]	D2 [mm]	L1 [mm]	I1 [mm]	I2 [mm]	S1 [mm]	Weight [g]
-32-20	2"	1.1/4"	46	29	68	25	20	70	826.32
-32-24	2"	1.1/2"	46	33	68	25	22	70	796.37
-32-32	2"	2"	46	46	70	25	25	70	737

Connection 1	Connection size 1	Connection 2	Connection size 2	Maximum operating pressure in bar	Article
External thread	1.1/2" BSP cyl.	External thread	1.1/2" BSP cyl.	200	12250899
External thread	1.1/2" BSP cyl.	External thread	1.1/4" BSP cyl.	200	11306169
External thread	1.1/2" BSP cyl.	External thread	1" BSP cyl.	200	12564678
External thread	1.1/2" BSP cyl.	External thread	3/4" BSP cyl.	200	12564677
External thread	1.1/4" BSP cyl.	External thread	1.1/4" BSP cyl.	200	11327332
External thread	1.1/4" BSP cyl.	External thread	1/2" BSP cyl.	200	12564675
External thread	1.1/4" BSP cyl.	External thread	1" BSP cyl.	200	11306148
External thread	1.1/4" BSP cyl.	External thread	3/4" BSP cyl.	200	12564676
External thread	1/2" BSP cyl.	External thread	1/2" BSP cyl.	400	1054503
External thread	1/2" BSP cyl.	External thread	1/4" BSP cyl.	400	11306008
External thread	1/2" BSP cyl.	External thread	3/8" BSP cyl.	400	931624
External thread	1/4" BSP cyl.	External thread	1/4" BSP cyl.	400	956201
External thread	1/4" BSP cyl.	External thread	1/8" BSP cyl.	400	1023043
External thread	1/8" BSP cyl.	External thread	1/8" BSP cyl.	400	1033407
External thread	1" BSP cyl.	External thread	1/2" BSP cyl.	250	1021932
External thread	1" BSP cyl.	External thread	1" BSP cyl.	250	931675
External thread	1" BSP cyl.	External thread	3/4" BSP cyl.	250	1021933
External thread	1" BSP cyl.	External thread	3/8" BSP cyl.	250	12564674
External thread	2" BSP cyl.	External thread	1.1/2" BSP cyl.	100	12564681
External thread	2" BSP cyl.	External thread	1.1/4" BSP cyl.	100	12564680
External thread	2" BSP cyl.	External thread	1" BSP cyl.	100	12564679
External thread	2" BSP cyl.	External thread	2" BSP cyl.	100	11449236
External thread	3/4" BSP cyl.	External thread	1/2" BSP cyl.	400	1032247
External thread	3/4" BSP cyl.	External thread	1/4" BSP cyl.	400	12564671
External thread	3/4" BSP cyl.	External thread	3/4" BSP cyl.	400	931659
External thread	3/4" BSP cyl.	External thread	3/8" BSP cyl.	400	12564672
External thread	3/4" BSP cyl.	External thread	5/8" BSP cyl.	400	12564673
External thread	3/8" BSP cyl.	External thread	1/4" BSP cyl.	400	1021929
External thread	3/8" BSP cyl.	External thread	1/8" BSP cyl.	400	12564668
External thread	3/8" BSP cyl.	External thread	3/8" BSP cyl.	400	944890
External thread	5/8" BSP cyl.	External thread	1/2" BSP cyl.	400	12564670
External thread	5/8" BSP cyl.	External thread	3/8" BSP cyl.	400	12564669
External thread	5/8" BSP cyl.	External thread	5/8" BSP cyl.	400	12564636

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.