

SKF High viscosity bearing grease with solid lubricants LGEM 2

- LGEM 2 is a high viscosity, mineral oil based grease using a lithium soap. Its content of molybdenum disulphide and graphite provides extra protection for harsh applications subjected to high loads, heavy vibrations and slow rotations. High oxidation stability
- Molybdenum disulphide and graphite provide lubrication even if the oil film breaks down

Typical applications:

- Rolling element bearings running at low speed and very high loads
- Jaw crushers
- Track laying machines
- Lift mast wheels
- Building machines such as mechanical rams, crane arms and crane hooks

Characteristics

Series: LGEM 2 Application: Lubrication - grease Temperature range: -20 / 120 °C Colour: Black Droping point: > 180 °C Thickener: Lithium/calcium Base oil type: Mineral oil Norm: NLGI 2 DIN standard: DIN 51825 KPF2K-20 Worked penetration 0.1mm: 265-295

Volume	Content	Packaging	Article
l de la companya de l	kg		
	5	Can	23766595
	18	Bucket	23766594
	180	Barrel	12174629
0.42		Cartridge	23766593

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Page 1/1

Tel: +31 88 855 81 75