

SKF High load high temperature and high viscosity bearing grease LGHB 2

- LGHB 2 is a high viscosity, mineral oil based grease, using the latest complex calcium-sulphonate soap technology. Formulated to withstand high temperatures and extreme loads, it is suitable for a wide range of applications, especially in the cement, mining and metals segments. This grease contains no additives and the extreme pressure properties arise from the soap structure. Excellent load capacity, anti-oxidation and corrosion protection even with large water ingress
- Withstands peak temperatures of 200°C



Typical applications:

- Steel on steel plain bearings
- Pulp and paper making machines
- Asphalt vibrating screens
- Continuous casting machines
- Sealed spherical roller bearings operating up to 150°C
- Work roll bearings in steel industry
- Mast rollers of fork lift trucks

Characteristics

Series: LGHB 2

Application: Lubrication - grease Temperature range: -20 / 150 °C

Colour: Brown

Droping point: > 220 °C Thickener: Calcium-complex Base oil type: Mineral oil

Norm: NLGI 2

DIN standard: DIN 51825 KP2N-20 Worked penetration 0.1mm: 265-295

Volume	Content	Packaging	Article
1	kg		
	5	Can	23766620
	18	Bucket	23766619
	50	Barrel	23766621
	180	Barrel	12174634
0.42		Cartridge	23766618

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.



Page 1/1

.RC0243_0049_JS_EN_25.04.2024