

## SKF Biodegradable bearing grease LGGB 2

- LGGB 2 is a biodegradable, low toxicity, synthetic ester oil based grease, using a lithium-calcium thickener. Its special formulation makes it most suitable for applications where environmental contamination is a concern. Compliance with current regulations on toxicity and biodegradability
- Good performance in applications with steel-on-steel spherical plain bearings, ball bearings and roller
- Good low temperature start-up performance
- Good corrosion inhibiting properties
- Suitable for medium to high loads

## Typical applications:

- Agricultural and forestry equipment
- Construction and earthmoving equipment
- Mining and conveying equipment
- Water treatment and irrigation
- Locks, dams, bridges
- Linkages, rod ends

## **Characteristics**

Series: LGGB 2

Application: Lubrication - grease Temperature range: -40 / 90 °C

Colour: Off-White Droping point: > 170 °C Thickener: Lithium/calcium Base oil type: Ester oil, synthetic

Norm: NLGI 2

DIN standard: DIN 51825 KPE2K-40 Worked penetration 0.1mm: 265-295

Volume	Content	Packaging	Article
1	kg		
	5	Can	23766617
	18	Bucket	24007309
0.42		Cartridge	23766616

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.



.RC0243\_0055\_JS\_EN\_25.04.2024