



SKF Low temperature extremely high speed bearing grease LGLT 2

- LGLT 2 is a fully synthetic oil based grease using lithium soap. Its unique thickener technology and low viscosity oil (PAO) provide excellent lubrication performances at low temperatures -50°C and extremely high speeds (n dm values of $1,6 \times 10^6$ can be reached). Low friction torque
- Quiet running
- Extremely good oxidation stability and resistance to water

Typical applications:

- Textile spinning spindles
- Machine tool spindles
- Instruments and control equipment
- Small electric motors used in medical and dental equipment
- In-line skates
- Printing cylinders
- Robots

Characteristics

Series: LGLT 2

Application: Lubrication - grease

Temperature range: $-50 / 110^{\circ}\text{C}$

Colour: Beige

Dropping point: $> 180^{\circ}\text{C}$

Thickener: Lithium

Base oil type: Synthetic (PAO)

Norm: NLGI 2

DIN standard: DIN 51825 K2G-50

Worked penetration 0.1mm: 265-295

Content kg	Packaging	Article
0.2	Pipe	23766632
1	Can	23766633
25	Bucket	24007310

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.