



SKF Extreme pressure (EP) grease LGEP 2

- LGEP 2 is mineral oil based, lithium soap thickened grease with extreme pressure additives. This grease provides good lubrication in general applications subjected to harsh conditions and vibrations. Excellent mechanical stability
- Extremely good corrosion inhibiting properties
- Excellent EP performance

Typical applications:

- Pulp and paper making machines
- Jaw crushers
- Traction motors for rail vehicles
- Dam gates
- Work roll bearings in steel industry
- Heavy machinery, vibrating screens
- Crane wheels, sheaves
- Slewing bearings

Packaging	Volume	Content	Application	Temperature range	Dropping point	Thickener	Article
	l	kg		°C	°C		
Barrel		50	Lubrication - grease	-20 / 110	> 180	Lithium	23766602
Barrel		180	Lubrication - grease	-20 / 110	> 180	Lithium	12174630
Bucket		18	Lubrication - grease	-20 / 110	> 180	Lithium	23766600
Can		1	Lubrication - grease	-20 / 110	> 180	Lithium	23766599
Can		5	Lubrication - grease	-20 / 110	> 180	Lithium	23766601
Cartridge	0.42		Lubrication - grease	-20 / 110	> 180	Lithium	23766598

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.