



MOLYKOTE G-N Plus Assembly paste



- Solid lubricant paste for the assembly and running-in of metal components.
 - High load-carrying capacity
- Low coefficient of friction
- Prevents frictional corrosion and scoring
- Protection from stick-slip
- Good anti-corrosion properties
- Reduces formation of fretting corrosion
- Simplifies dismantling processes.

Characteristics

Series: G-N Plus

Temperature range: -25 / 450 °C

Colour: Black

Application

- Press-fit production of all types of machine elements, as a running-in lubricant for new machines and gear-boxes; Permanent lubrication of machine elements that are moved only rarely or slightly and also for drilling, sawing and thread cutting; Used successfully for lubricating threaded spindles, splined shafts, toothed gears, worm and transmission gears, screws, valves, pumps, machine-tool guides and also for the tightening and fitting of roller bearings, washers, wheels, flanges and bolts.

Technical Information

Temperature Range:

- From -25 to +450°C

Content kg	Packaging	Article
0.1	Pipe	23164851
0.1	Pipe	23360988
0.25	Can	23360989
0.5		10020658
1		10020657

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.