

SKF Hydraulic pump series 729124



The 729124 pump is suitable for use with hydraulic nuts (smaller than or equal to HMV 54E) and for mounting and dismantling bearings or components where a maximum pressure of 100 MPa (14 500 psi) is required. The pump is supplied with 1500 mm (59 in.) pressure hose, quick connect coupling and mating nipple and pressure gauge. The pump is filled with SKF Mounting Fluid LHM 300 and is supplied with an extra litre of fluid.

Features:

- Oil container capacity 250 cm³ [15 in.³]
- Fitted with a pressure gauge
- Packed in a sturdy protective case



Applications:

- SKF hydraulic nuts smaller than or equal to HMV 54E
- Oil injection applications where the maximum pressure is 100 MPa (14 500 psi)
- For applications where space does not permit the use of a quick connect coupling and nipple, such as AOH sleeves, a special pump design is available (SKF 729124 A)

Characteristics

Series: 729124

Release/Descent Control Valve: No

Relief valve: No

Directional control valve: No

Description	Article
Hydraulic pump 729124	23759745
Hydraulic pump with THGD 100D digital pressure gauge 729124 DU	23759746

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.