

FILTRATION GROUP Low-pressure filter duplex type Pi 2100



Characteristics

Series: Pi 2100

Temperature range [°C]: -10 / 120 °C

Code digit	Size	Max. operating pressure bar	Connection	Valve type	With dirt indicator	Voltage	Filter element material	Filter fineness μm	Article
	40		1" BSP cyl.	No bypass	Optical 2,2 bar				13522047
	40		1" BSP cyl.	No bypass	Optical/ Electrical 2,2 bar	250VAC/200VDC			13522048
Pi 21004-057	40	63	1" BSP cyl.	Bypass 3,5 bar	Optical 2,2 bar				13522045
Pi 21004-058	40	63	1" BSP cyl.	Bypass 3,5 bar	Optical/ Electrical 2,2 bar	250VAC/200VDC			13522046
Pi 21004-058 * E79769308	40	63	1" BSP cyl.	Bypass 3,5 bar	Optical/ Electrical 2,2 bar	250VAC/200VDC	Metal mesh	25	13801086
	63		1" BSP cyl.	Bypass 3,5 bar	Optical 2,2 bar				13522049
	63		1" BSP cyl.	No bypass	Optical 2,2 bar				13522051
	63		1" BSP cyl.	No bypass	Optical/ Electrical 2,2 bar	250VAC/200VDC			13522052
Pi 21006-058	63	63	1" BSP cyl.	Bypass 3,5 bar	Optical/ Electrical 2,2 bar	250VAC/200VDC			13522050
	100		1" BSP cyl.	No bypass	Optical 2,2 bar				13522055
Pi 21010-069	100	63	1" BSP cyl.		Optical/ Electrical 2,2 bar	250VAC/200VDC			13522056
Pi 21010-057	100	63	1" BSP cyl.	Bypass 3,5 bar	Optical 2,2 bar				13522053
Pi 21010-058	100	63	1" BSP cyl.	Bypass 3,5 bar	Optical/ Electrical 2,2 bar	250VAC/200VDC			13522054
	160		1.1/2" BSP cyl.	No bypass	Optical 2,2 bar				13522059
Pi 21016-069	160	32	1.1/2" BSP cyl.		Optical/ Electrical 2,2 bar	250VAC/200VDC			13522060
Pi 21016-057	160	32	1.1/2" BSP cyl.	Bypass 3,5 bar	Optical 2,2 bar				13522057
Pi 21016-058	160	32	1.1/2" BSP cyl.	Bypass 3,5 bar	Optical/ Electrical 2,2 bar	250VAC/200VDC			13522058
	250		1.1/2" BSP cyl.	No bypass	Optical 2,2 bar				13522063
	250		1.1/2" BSP cyl.	No bypass	Optical/ Electrical 2,2 bar	250VAC/200VDC			13522064
Pi 21025-057	250	32	1.1/2" BSP cyl.	Bypass 3,5 bar	Optical 2,2 bar				13522061
Pi 21025-058	250	32	1.1/2" BSP cyl.	Bypass 3,5 bar	Optical/ Electrical 2,2 bar	250VAC/200VDC			13522062
	400		1.1/2" BSP cyl.	Bypass 3,5 bar	Optical 2,2 bar				13522065
	400		1.1/2" BSP cyl.	No bypass	Optical 2,2 bar				13522067
Pi 21040-069	400	32	1.1/2" BSP cyl.		Optical/ Electrical 2,2 bar	250VAC/200VDC			13522068
Pi 21040-058	400	32	1.1/2" BSP cyl.	Bypass 3,5 bar	Optical/ Electrical 2,2 bar	250VAC/200VDC			13522066

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.