



FILTRATION GROUP High-pressure filter type Pi 4000

Characteristics

Series: Pi 4000

Temperature range [°C]: -10 / 120 °C

Code digit	Size	Max. operating pressure bar	Connection	Valve type	With dirt indicator	Voltage	Article
	40		1/2" BSP cyl.	Bypass 7 bar	No		13522367
	40		1/2" BSP cyl.	No bypass	No		13522366
	40		1/2" BSP cyl.	No bypass	Optical 5 bar		13522370
Pi 40004-015	40	400	1/2" BSP cyl.		Optical/Electrical 5 bar	250VAC/200VDC	13522371
Pi 40004-012	40	400	1/2" BSP cyl.	Bypass 7 bar	Optical 5 bar		13522368
Pi 40004-013	40	400	1/2" BSP cyl.	Bypass 7 bar	Optical/Electrical 5 bar	250VAC/200VDC	13522369
Pi 40006-010	63	400	3/4" BSP cyl.		No		13522372
Pi 40006-014	63	400	3/4" BSP cyl.		Optical 5 bar		13522376
Pi 40006-015	63	400	3/4" BSP cyl.		Optical/Electrical 5 bar	250VAC/200VDC	13522377
Pi 40006-011	63	400	3/4" BSP cyl.	Bypass 7 bar	No		13522373
Pi 40006-012	63	400	3/4" BSP cyl.	Bypass 7 bar	Optical 5 bar		13522374
Pi 40006-013	63	400	3/4" BSP cyl.	Bypass 7 bar	Optical/Electrical 5 bar	250VAC/200VDC	13522375
	100		1" BSP cyl.	Bypass 7 bar	Optic		13522380
	100		1" BSP cyl.	No bypass	Optical 5 bar		13522382
Pi 40010-010	100	400	1" BSP cyl.		No		13522378
Pi 40010-015/PIS 3152	100	400	1" BSP cyl.		Optical/Electrical 3,7 / 5,0 bar	250VAC/200VDC	13805604
Pi 40010-015	100	400	1" BSP cyl.		Optical/Electrical 5 bar	250VAC/200VDC	13522383
Pi 40010-011	100	400	1" BSP cyl.	Bypass 7 bar	No		13522379
Pi 40010-013	100	400	1" BSP cyl.	Bypass 7 bar	Optical/Electrical 5 bar	250VAC/200VDC	13522381
	160		1.1/4" BSP cyl.	No bypass	No		13522384
Pi 40016-014	160	400	1.1/4" BSP cyl.		Optical 5 bar		13522388
Pi 40016-015	160	400	1.1/4" BSP cyl.		Optical/Electrical 5 bar	250VAC/200VDC	13522389
Pi 40016-011	160	400	1.1/4" BSP cyl.	Bypass 7 bar	No		13522385
Pi 40016-012	160	400	1.1/4" BSP cyl.	Bypass 7 bar	Optical 5 bar		13522386
Pi 40016-013	160	400	1.1/4" BSP cyl.	Bypass 7 bar	Optical/Electrical 5 bar	250VAC/200VDC	13522387
	250		1.1/2" BSP cyl.	Bypass 7 bar	No		13522391
	250		1.1/2" BSP cyl.	No bypass	No		13522390
	250		1.1/2" BSP cyl.	No bypass	Optical 5 bar		13522394
Pi 40025-015	250	400	1.1/2" BSP cyl.		Optical/Electrical 5 bar	250VAC/200VDC	13522395
Pi 40025-012	250	400	1.1/2" BSP cyl.	Bypass 7 bar	Optical 5 bar		13522392
Pi 40025-013	250	400	1.1/2" BSP cyl.	Bypass 7 bar	Optical/Electrical 5 bar	250VAC/200VDC	13522393
	400		Flange connection DN38	Bypass 7 bar	No		13522397
	400		Flange connection DN38	No bypass	No		13522396
	400		Flange connection DN38	No bypass	Optical 5 bar		13522400
Pi 40040-015 FL	400	400	Flange connection DN38		Optical/Electrical 5 bar	250VAC/200VDC	13522401

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Code digit	Size	Max. operating pressure bar	Connection	Valve type	With dirt indicator	Voltage	Article
Pi 40040-012 FL	400	400	Flange connection DN38	Bypass 7 bar	Optical 5 bar		13522398
Pi 40040-013 FL	400	400	Flange connection DN38	Bypass 7 bar	Optical/Electrical 5 bar	250VAC/200VDC	13522399

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.