



FILTRATION GROUP High-pressure filter stainless steel type Pi 480

Characteristics

Series: Pi 480

Temperature range [°C]: -10 / 120 °C

Code digit	Size	Max. operating pressure bar	Connection	Valve type	With dirt indicator	Voltage	Article
	40		1" BSP cyl.	No bypass	Optical/Electrical 5 bar	230VAC/230VDC	13522592
Pi 48004-060/G1	40	450	1" BSP cyl.		No		13522593
Pi 48004-014/G1	40	450	1" BSP cyl.		Optical 5 bar		13522591
	63		1" BSP cyl.	No bypass	Optical 5 bar		13522594
	63		1" BSP cyl.	No bypass	Optical/Electrical 5 bar	230VAC/230VDC	13522595
Pi 48006-060/G1	63	450	1" BSP cyl.		No		13522596
	100		1" BSP cyl.	No bypass	No		13522599
	100		1" BSP cyl.	No bypass	Optical 5 bar		13522597
	100		1" BSP cyl.	No bypass	Optical/Electrical 5 bar	230VAC/230VDC	13522598
	160		1.1/2" BSP cyl.	No bypass	No		13522601
	160		1.1/2" BSP cyl.	No bypass	Optical/Electrical 5 bar	230VAC/230VDC	13522600
	250		1.1/2" BSP cyl.	No bypass	Optical 5 bar		13522602
	250		1.1/2" BSP cyl.	No bypass	Optical/Electrical 5 bar	230VAC/230VDC	13522603
Pi 48025-060	250	250	1.1/2" BSP cyl.		No		13522604

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.