

DANFOSS Orbitmotor H Series



Characteristics

Series: H

Direction of rotation: Clockwise and counterclockwise

Mounting flange	Drive shaft	Displacement cm ³ /r	Max. operating pressure bar	Inlet port	Outlet port	Position oil ports	Code	Article
SAE-A 2 bolts	Cylindrical 25 mm	36	124	BSP female 1/2 "BSP	BSP female 1/2 "BSP	Side	101-2158	969338
SAE-A 2 bolts	Cylindrical 25 mm	46	124	BSP female 1/2 "BSP	BSP female 1/2 "BSP	Side	101-2124	969524
SAE-A 2 bolts	Cylindrical 25 mm	59	124	BSP female 1/2 "BSP	BSP female 1/2 "BSP	Side	101-2159	969621
SAE-A 2 bolts	Cylindrical 25 mm	74	124	BSP female 1/2 "BSP	BSP female 1/2 "BSP	Side	101-2160	969648
SAE-A 2 bolts	Cylindrical 25 mm	96	124	BSP female 1/2 "BSP	BSP female 1/2 "BSP	Side	101-2125	969737
SAE-A 2 bolts	Cylindrical 25 mm	120	124	BSP female 1/2 "BSP	BSP female 1/2 "BSP	Side	101-2161	969796
SAE-A 2 bolts	Cylindrical 25 mm	146	117	BSP female 1/2 "BSP	BSP female 1/2 "BSP	Side	101-2162	969931
SAE-A 2 bolts	Cylindrical 25 mm	159	114	BSP female 1/2 "BSP	BSP female 1/2 "BSP	Side	101-2148	970050
SAE-A 2 bolts	Cylindrical 25 mm	185	110	BSP female 1/2 "BSP	BSP female 1/2 "BSP	Side	101-2149	970131
SAE-A 2 bolts	Cylindrical 25 mm	231	100	BSP female 1/2 "BSP	BSP female 1/2 "BSP	Side	101-2163	970158
SAE-A 2 bolts	Cylindrical 25 mm	293	93	BSP female 1/2 "BSP	BSP female 1/2 "BSP	Side	101-2150	970174
SAE-A 2 bolts	Cylindrical 25 mm	370	86	BSP female 1/2 "BSP	BSP female 1/2 "BSP	Side	101-2164	970182

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.