


DANFOSS CETOP plunger 2A



Characteristics
Version: Flangeable
Size: NG6/Cetop 3
Type of valve: 4/2
Operation: Electrical



Model	Max. operating pressure	Max. oilflow	Voltage	Max. pressure on T	Electrical connection	Number of magnets per valve	Options	Article
	bar	l/min		bar				
Conventional	350	80	12 VDC	210	DIN-Connector	1		1033803
Conventional	350	80	24 VDC	210	DIN-Connector	1		1033804
Conventional	350	80	24 VDC	210	DIN-Connector	1	Low leakage	1039736
Conventional	350	80	110 VAC 50HZ	210	DIN-Connector	1		1033806
Conventional	350	80	196 VDC	210	DIN-Connector	1		1039733
Conventional	350	80	230 VAC 50HZ	210	DIN-Connector	1		1039726
Conventional	315	120	12 VDC	160	DIN-Connector	1		1041583
Conventional	315	120	24 VDC	160	DIN-Connector	1		1033899
Conventional	315	120	110 VAC 50HZ	120	DIN-Connector	1		1033911
Conventional	315	120	230 VAC 50HZ	120	DIN-Connector	1		1033912

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.