

WALVOIL Monobloc valve HC-M45

Characteristics

Number of sections: 6

Operation: Manual

Pressure feed-through: Yes



Model	Max. operating pressure bar	Max. oilflow l/min	Max. pressure on T bar	Connections	Article
Conventional	350	45	20	P,A,B,T,HPCO: 3/8"BSP	11539847
Conventional	350	45	20	P,A,B,T,HPCO: 3/8"BSP	11538521
Conventional	350	45	20	P,A,B,T,HPCO: 3/8"BSP	11539845
Conventional	350	45	20	P,A,B,T,HPCO: 3/8"BSP	11538525
Conventional	350	45	20	P,A,B,T,HPCO: 3/8"BSP	11545183
Conventional	350	45	20	P,A,B,T,HPCO: 3/8"BSP	11539844
Conventional	350	45	20	P,A,B,T,HPCO: 3/8"BSP	11542256
Conventional	350	45	20	P,A,B,T,HPCO: 3/8"BSP	11545188
Conventional	350	45	20	P,A,B,T,HPCO: 3/8"BSP	11539864
Conventional	350	45	20	P,A,B,T,HPCO: 3/8"BSP	11545190
Conventional	350	45	20	P,A,B,T,HPCO: 3/8"BSP	11539870
Conventional	350	45	20	P,A,B,T,HPCO: 3/8"BSP	11545194
Conventional	350	45	20	P,A,B,T,HPCO: 3/8"BSP	11539875
Conventional	350	45	20	P,A,B,T,HPCO: 3/8"BSP	11532662

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.