



SILVENT Air knives

Characteristics

Type: 374 F

Outlet pattern	Thread type	Connection	Nozzle material	Blowing force	Air consumption	Max. temperature	Replaces open pipe Ø	Weight	Article
		in		N	Nm³/h	°	mm	kg	
Flat	Parallel (G)	3/8	Zinc	20.4	102	70	10	0.608	23177221
Flat	Parallel (G)	3/8	Stainless steel	6.7	34	400	6	0.332	11952199
Flat	Parallel (G)	3/8	Zinc	22	120	70	10	0.695	23177261
Flat	Parallel (G)	3/8	Zinc	33	180	70	12	1.005	23177262
Flat	Parallel (G)	3/8	Zinc	11	60	70	7	0.36	23177260
Flat	Parallel (G)	3/8	Zinc	13.6	68	70	8	0.414	23177220
Flat	Parallel (G)	3/8	Zinc	19.8	117	70	10	0.286	11952204
Flat	Parallel (G)	3/8	Stainless steel	20.4	102	400	10	0.892	11952201
Flat	Parallel (G)	3/8	Stainless steel	13.6	68	400	8	0.612	11952200
Flat	Parallel (G)	3/8	Zinc	6.7	34	70	6	0.224	23177219
Flat	Parallel (G)	3/8	Zinc	13.2	78	70	8	0.206	11952203
Flat	Parallel (G)	1	Zinc	6.6	39	70	6	0.127	11952202
Flat	Parallel (G)	1	Stainless steel	76	464	400	20	2.865	11952209

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.